

NIST Calibration Program
Calibration Services Users Guide
SP 250 Appendix
Fee Schedule – February 24, 2014

Calibration Services:

Dimensional

Mechanical

Thermodynamic

Optical Radiation

Ionizing Radiation

Electromagnetic

Time and Frequency



National Institute of
Standards and Technology
U.S. Department of Commerce

Table of Contents

CHAPTER 1	1
POLICIES	1
A. Introduction	1
B. ProForma Invoice	1
C. Types of Calibration Services	1
D. Criteria for Quality Assurance	2
E. Quality	2
F. Fees	2
G. Reports of Calibration/Test Results	2
H. Traceability	2
I. Reporting Measurement Uncertainty	3
J. Use of Metric (SI) Units	3
K. Reference to NIST in Advertisements	3
L. Disclaimer	4
M. Questions and Inquires	4
N. Contracts and Signed Statements	4
O. Use of NIST Instrumentation at User's Facility	4
CHAPTER 2	5
ORDERING INSTRUCTIONS FOR DOMESTIC CUSTOMERS	5
A. Customer Inquires	5
B. Prearrangements and Scheduling	5
C. Purchase Orders	5
D. Remit to	6
E. Shipping, Insurance, and Risk of Loss	7
F. Turnaround Time	7
G. Customer Checklist	7
CHAPTER 3	9
SPECIAL INSTRUCTIONS FOR FOREIGN CUSTOMERS	9
A. Foreign Inquires	9
B. Criteria for Providing Service	9
C. Special Instructions	9
D. Shipping Charges	11
CHAPTER 4	12
DIMENSIONAL MEASUREMENTS	12
A. Length Measurements	12
B. Diameter and Roundness Measurements	14
C. Complex Dimensional Standards	15
E. Optical Reference Planes and Roundness Standards	17

F.	Angular Measurements	18
G.	Laser Measurements	18
H.	Surface Texture	19

CHAPTER 5 **20**

MECHANICAL MEASUREMENTS		20
A.	Hydrometers	20
B.	Volume and Density	20
C.	Flow Measurements	21
D.	Flow Measurements at Cryogenic Temperatures	21
O.	Air Speed Measurements	22
F.	Mass Standards	22
G.	Force Measurements	23
H.	Vibration Measurements	24
I.	Acoustic Measurements	25

CHAPTER 6 **26**

THERMODYNAMIC QUANTITIES		26
A.	Pressure Measurements	26
B.	Vacuum, Low Pressure and Leak Measurements	26
C.	Laboratory and Industrial-Grade Thermometers	28
D.	Thermocouples, Thermocouple Materials, Thermometer Indicators	29
E.	Resistance Thermometry	30
F.	Radiance Temperature Measurements	32
G.	Humidity Measurements	33
H.	Thermal Resistance Measurements	34

CHAPTER 7 **35**

OPTICAL RADIATION MEASUREMENTS		35
A.	Photometric Measurements	35
B.	Ozone Measurements	36
C.	Optical Properties of Materials Measurements	36
D.	Surface Color and Appearance	37
E.	Spectroradiometric Measurements	37
F.	Radiometric Standards in the Ultraviolet	39
G.	Laser and Optoelectronic Components Used with Lasers	40

CHAPTER 8 **42**

IONIZING RADIATION MEASUREMENTS		42
A.	Radioactivity Sources	42
B.	Neutron Sources and Neutron Dosimetry	43
C.	Dosimetry of X-Rays, Gamma-Rays, and Electrons	43
D.	Dosimetry for High-Dose Applications	44

CHAPTER 9 **46**

ELECTROMAGNETIC MEASUREMENTS	46
-------------------------------------	-----------

A.	Resistance Measurements	46
B.	Impedance Measurements (Except Resistors)	48
C.	Voltage Measurements	50
D.	Precision Ratio Measurements	52
E.	Phase Meters and Standards and VOR Measurements	54
F.	Power and Energy Measurements, Low-Frequency	55
G.	RF, Microwave and Millimeter-Wave Measurements	56
H.	Electromagnetic Field Strength and Antenna Measurements	60
I.	High-speed Repetitive Waveform Measurements	61
J.	Pulse Waveform Measurements	61
 CHAPTER 10		 62
TIME AND FREQUENCY MEASUREMENTS		62
A.	Broadcast and Measurement Services	62
B.	Calibration and Characterization of Oscillators and Amplifiers	63
C.	Test of PM/AM Noise Measurement Systems	63
 CHAPTER 11		 64
SEMINARS		64

CHAPTER 1

POLICIES

A. Introduction

The calibration services of the National Institute of Standards and Technology (NIST) are designed to help the makers and users of precision instruments achieve the highest possible levels of measurement quality and productivity. The services listed in this Fee Schedule constitute the highest order of calibration services available in the United States. They directly link a customer's precision equipment or transfer standards to national and international measurement standards. These services are offered to public and private organizations and individuals alike.

For more specific information, the NIST Calibration Services Users Guide, SP 250, contains data on uncertainty and other technical references. Copies are available upon request or consult our website (see Section L of this chapter).

B. ProForma Invoice

Please be advised that for non-U.S. government agencies, starting 01 January 2013, a new legal document (Calibration Service Pro Forma Invoice) containing the NIST calibration service terms and conditions are required for all calibration services. This document is a Calibration Cooperative Research and Development Agreement (C-CRADA) between your company and NIST. In general, this C-CRADA protects your calibration information as well as providing you with a firm price quote, explaining invoicing information, and information on the NIST quality system and traceability. In addition to the legal terms and conditions, the Calibration Service Pro Forma Invoice is used in two primary ways: 1) to create a firm price quote prior to submission of a company purchase order or 2) to create a firm price quote after receipt of a company purchase order. In either case, a signed copy of the Calibration Service Pro Forma Invoice by the authorized company representative is required by NIST. The terms and conditions of the Calibration Service Pro Forma Invoice supersede any conflicting and/or additional terms and conditions contained in a company's purchase order.

For U.S. government agencies, an agreement is required in lieu of the Calibration Service Pro Forma Invoice. Please contact Nancy Selepak (nancy.selepak@nist.gov) for assistance.

C. Types of Calibration Services

- Calibration Services
- Special Tests
- Measurement Assurance Programs (MAPs)

NIST provides Calibration Services using well-characterized, stable and predictable measurement processes. NIST calibrates instruments and devices that are metrologically suitable as reference or transfer standards.

Special Tests are so designated for one or more of the following reasons: (1) the specific type of calibration is seldom requested, thus precluding the maintenance of a large statistical base for characterizing the measurement process; (2) the test requested is unique; or (3) the service is still under development – meaning the measurement or calibration methods are still being perfected, or all the quality-control documentation has not been completed.

Measurement Assurance Programs are quality control programs for calibrating a customer's entire measurement system. In a typical MAP, a stable artifact or set of artifacts called transfer standards are first measured by NIST and then sent to a customer's laboratory for a series of measurements. The transfer standards are then returned to NIST for re-measurement, along with the participating laboratory's results. NIST reports its comparative findings to the customer and, when necessary, offers guidance on achieving and

maintaining measurement quality. Successful use of a NIST MAP requires that the customer make periodic measurements of in-house check standards to estimate their measurement process uncertainty and to ensure that the measurement process remains in a state of statistical control. Unless a laboratory has a measurement quality assurance program to monitor its own measurement process parameters continuously, there is no value in participating in a MAP. In fact, NIST recommends that its customers establish and use a measurement quality assurance program to monitor their measurement parameters, whether or not they participate in a MAP.

D. Criteria for Quality Assurance

All the measurement services listed in this document meet rigorous criteria for quality assurance. Calibration Services and MAPs satisfy the most demanding and explicit requirements in that they are carried out regularly under pre-established and well-defined conditions; the measurement processes involved are well-characterized, stable, and statistically controlled; and quality-control procedures are well-defined and strictly followed. Furthermore, each Calibration Service or MAP is planned and documented to permit continuity of service over time.

E. Quality

NIST has implemented a quality system for its measurement services. The NIST Quality System, www.nist.gov/qualitysystem/ (NIST QS) comprises policies and procedures that are documented in the NIST Quality Manual (NIST QM). NIST commits that the NIST QS be, to the extent allowed by statute and regulation, in conformity with the international standard ISO/IEC 17025 and the relevant requirements of ISO Guide 34 as they apply to the Standard Reference Materials® (SRMs) and related services that NIST delivers. In general the scope of the NIST quality system for measurement services encompasses all services listed in the NIST Special Publication (SP) 250, NIST Calibration Services Users Guide and the NIST Special Publication (SP) 260, Standard Reference Materials Catalog. In particular, specific services covered by the NIST QS are those that are declared in conformity by the NIST Measurement Services Advisory Group (MSAG). For further details, consult the NIST Quality Manual for Measurement Services (NIST-QM-I).

F. Fees

NIST recovers the cost of providing calibration services by charging a fee for each calibration performed. The costs of services are published in the Fee Schedule, which is updated and published annually to reflect changes in prices and services. Even so, the cost of many services varies according to your exact calibration specifications; you must therefore provide the technical contact with an exact description of work before receiving a price quote.

NOTE: Fees for NIST services do not include shipping costs or insurance.

G. Reports of Calibration/Test Results

Reports on calibrations or other services are the property of the customer. Copies are supplied to other parties only as required by federal law or requested in writing by the customer. The results of calibrations and tests performed by NIST apply only to the specific instrument or standard at the time of test unless otherwise clearly stated.

H. Traceability

The primary purpose of the NIST Policy on Traceability is to state the NIST role with respect to traceability. The Policy presents the definition of measurement traceability used by NIST, and clarifies the roles of NIST

and others in achieving traceability of measurement results for measurements both internal and external to NIST.

The NIST Policy on Traceability also addresses the role of NIST in providing its customers with the tools they need (a) to assist them in establishing traceability of their measurement results, and (b) to assess the claims of traceability made by others. This is achieved directly through the provision of NIST measurement-related products and services, through collaboration with relevant organizations, through development and dissemination of technical information on traceability, and through conducting coordinated outreach programs.

Merely having an instrument or artifact calibrated at NIST is not enough to make the measurement result traceable to reference standards developed and maintained by NIST. To establish traceability to such reference standards, there must be an unbroken chain of comparisons and each provided measurement must be accompanied by a statement of uncertainty. The measurement system by which values are transferred must be clearly understood and under control. The dates and details of each link in the chain must also be provided.

Although NIST supports making the user aware of traceability and provides the user with details as to how traceability is established, NIST does not allow the prominent display of its name on proprietary products or in the advertising of them (See Section J of this chapter).

I. Reporting Measurement Uncertainty

To ensure that NIST uncertainty statements are consistent across the organization and with international practice, NIST policy requires that all NIST measurements be accompanied by statements of uncertainty as discussed in NIST Technical Note 1297¹.

NIST reports its calibration results, with the measurement values accompanied by the uncertainties associated with the methods, operators, and environment at NIST. Users of these calibration services will make their own measurements with the calibrated instruments or artifacts. In addition to the uncertainty indicated by NIST, other uncertainties are inherent in the instrument, associated with the method or protocol in using the instrument, with the operator of the instrument, and with the physical environment (pressure, temperature, humidity, etc.) in which the measurements are made. Thus, the measurements made with the calibrated instruments or artifacts by organizations outside of NIST have total uncertainty budgets associated with them, only one component of which is the uncertainty reported to them by NIST.

J. Use of Metric (SI) Units

In accordance with the Metric Conversion Act of 1975 as amended by Section 5164 of the Omnibus Trade and Competitiveness Act of 1988 and as required by related provisions of the Code of Federal Regulations, the National Institute of Standards and Technology (NIST) uses the modern metric system of measurement units (International System of Units—SI) in all publications. When the field of application or the special needs of users of NIST publication require the use of non-SI units, the values of quantities are first stated in the SI units and the corresponding values expressed in non-SI units follow in parentheses. Copies of NIST SP 811³ are available upon request (see Section L) or on the web site: www.nist.gov/pml/pubs/

K. Reference to NIST in Advertisements

The NIST measurement/test results or reports shall not be used to indicate or imply that NIST approves, recommends, or endorses the manufacturer, supplier, or user of any instruments or standards or that NIST in any way guarantees or predicts the future performance of items after calibration or test. No reference shall be made to NIST or to reports or results furnished by NIST in any advertising or sales promotions, which would indicate or imply that NIST approves, recommends, or endorses any proprietary product or proprietary material.

L. Disclaimer

Commercial products, materials, and instruments, are identified in our communications and documents for the sole purpose of adequately describing experimental or test procedures. In no event does such identification imply recommendation or endorsement by NIST of a particular product; nor does it imply that a named material or instrument is necessarily the best available for the purpose it serves.

M. Questions and Inquires

The NIST Calibration Services website is intended to make the task of selecting and ordering an appropriate calibration service as quick and easy as possible. Nevertheless, when questions arise you should contact NIST for immediate clarification.

General inquiries about the NIST calibration services, assistance in determining the availability of services, and requests for complimentary copies of the Guide for the International System of Units (SP 811), and Guidelines for Evaluating and Expressing the Uncertainty of NIST Measurement Results (TN 1297) are to be addressed to:

PML Calibration Services
National Institute of Standards and Technology
100 Bureau Drive, Stop 8363
Gaithersburg, MD 20899-8363
United States of America
Telephone: (301) 975-2200
Fax: (301) 975-2950
Email: calibrations@nist.gov
Internet: www.nist.gov/calibrations/

For technical questions concerning a specific service, directly contact the NIST staff member responsible for that calibration area.

N. Contracts and Signed Statements

As an agency of the United States Federal Government, Department of Commerce, the National Institute of Standards and Technology attests solely to the provisions described above. Receipt of orders by NIST does not imply acceptance of any provisions set forth in the order that are contrary to the policy, practice, or regulations of NIST or the U.S. Government. In general, NIST will not sign any affidavits, acknowledgement forms, or other documents that may be required by any domestic or foreign entity for policy governing procurement of goods and services.

O. Use of NIST Instrumentation at a User's Facility

The delivery of certain measurement services requires that NIST equipment be loaned to the customer for on-site measurements and/or calibrations. The customer agrees to be responsible for the equipment once it leaves NIST until it is returned to NIST's possession. The User will obtain appropriate liability insurance, including property damage insurance, and will be required to present evidence of insurance coverage for the equipment in an amount not less than \$100,000, or alternatively, not less than the amount specified by NIST in the documentation accompanying the equipment.

CHAPTER 2

ORDERING INSTRUCTIONS FOR DOMESTIC CUSTOMERS

A. Customer Inquires

General customer inquiries for information or clarifications about the NIST calibration services should be directed as follows:

PML Calibration Services
National Institute of Standards and Technology
100 Bureau Drive, Stop 8363
Gaithersburg, MD 20899-8363
301-975-2200 phone
301-975-2950 fax
calibrations@nist.gov

B. Prearrangements and Scheduling

Services should be arranged in advance, beginning with direct contact with a NIST technical staff member responsible for the desired service. Use the appropriate technical section of the Users Guide or Fee Schedule to determine whom to contact. This advance communication may answer your questions, clarify the policies and procedures briefly described here, and will permit you to schedule a tentative calibration date. Following the initial communication, you must complete and submit a purchase order and prepare to ship the item according to the procedures described below or agreed upon with the technical contact. If a calibration is scheduled far in advance, the item should not be shipped until shortly before the scheduled date; you must submit the purchase order (complete with the name and number of the desired service) before a firm calibration date can be assigned. When NIST receives your purchase order and assigns a firm service date, your order will be confirmed by the technical contact.

C. Purchase Orders

Before you ship an item for calibration, send a purchase order to the address listed in the appropriate technical section. The purchase order must:

1. State both the name and number of the NIST service (listed in this Fee Schedule as the “Service ID Number”) being requested. **FAILURE TO INCLUDE THE SERVICE ORDER NUMBER WILL SERIOUSLY IMPEDE SCHEDULING AND SERVICE.**
2. Clearly identify the item(s) being sent for calibration, including any serial number(s) or model number(s).
3. Give the name, address, and telephone number of your company’s procurement officer, purchasing agent or other administrative/financial authority.
4. Give the name, address, and telephone number of your company’s technical contact, if different from above.
5. List separately the instructions and address for return shipment, insurance, mailing address for the calibration/test report, and billing address. (Federal or state agency requests for calibration services should be accompanied by a document authorizing that the cost of the service be billed to the agency).
6. Clearly state any special or necessary conditions of test, such as operating frequency or temperature.

7. Clearly state the customer identification number; i.e., customer's employer identification number (EIN) for individuals; tax identification number (TIN) for organizations; or agency location code (ALC) for government customers.
8. If the calibration or test report is to be handled in a special manner, give instructions on the purchase order.

NOTE: Receipt of orders by NIST does not imply acceptance of any provisions set forth in the order that are contrary to the policy, practice, or regulations of NIST or the U.S. Government. In general, NIST will not sign any affidavits, acknowledgement forms, or other documents that may be required by company policy governing the procurement of goods and services.

D. Remit to

Payment Terms: Net 30 days

No discounts are allowed for early payment.

PAY.GOV

For NIST invoices, electronic payments can be submitted through Pay.gov by ACH, VISA, MasterCard, Discover, American Express or debit card. Go to www.pay.gov. Bypass the user id and password section; you do not need to be registered with Pay.gov to make a payment against our invoices. To locate the payment forms click on "by Agency Name" on the left hand side of the menu bar. Find and select the National Institute of Standards and Technology. Choose the appropriate NIST payment form that best fits your invoice. Complete all required fields and submit your payment.

Note: For ACH payments, please verify with your banking institution that your account is set up to have ACH payments processed.

Remit to address:

NIST Lockbox accepts check payments for NIST. Please use the following address for all NIST payments:

NIST
P.O. Box 301505
Los Angeles, CA 90030-1505

Please remember that all checks must be drawn on a United States bank and made payable in US dollars. In addition, please continue to reference the NIST invoice/receivable number on the check stub.

Other Forms of Payment

In addition to checks, NIST also accepts VISA, MasterCard, Discover, and American Express. Customers can supply their credit card information and fax a copy of the invoice to Accounts Receivable at 310/975-8943 or mail the information to:

NIST
Mail Stop 1624
100 Bureau Drive
Gaithersburg, MD 20899-1624

NIST Federal Identification Number: 530-20-5706

NIST DUNS Number: 929956050

W-9 Mail to:
NIST
Accounts Receivable
Stop 1624
Gathersburg, MD 20899-1624

E. Shipping, Insurance, and Risk of Loss

Ship the instrument or standard to the mailing address of the technical group providing the service. Please take note that the mailing address is not the same for every technical group.

Please adhere rigorously to the following procedures:

1. Ship only items in good repair. Apparatus in disrepair will not be calibrated. If defects are found, after calibration has begun, the procedure will be terminated, a report issued, and a charge levied for work completed.
2. Use strong, reusable packing materials and containers marked clearly and indelibly on the outside with the requestor's name, address and the following notation: **REUSABLE CONTAINER, DO NOT DESTROY.**
3. Follow any special shipping procedures given in the technical sections of the Calibration Services Users Guide, particularly those sections covering radiation and dosimetry measurements.
4. Insure the shipments to and from NIST and clearly state the method of return shipment. NIST will not assume liability for loss or damage unless such loss and damage result solely from the negligence of NIST personnel. If return shipment by parcel post is requested or is suitable, NIST will prepay the return shipment but will not insure it. When no shipping or insurance instructions are furnished, NIST will return the shipment by common carrier, collect and uninsured.
5. Shipments to NIST must be at FOB destinations (customer pays for shipping).
6. Return shipments are sent FOB origin (customer pays for shipping).

NOTE: Fees for NIST services do not include shipping cost or insurance.

F. Turnaround Time

Normal turnaround time for NIST calibration services varies greatly—usually from several weeks to several months depending on the type of service requested, and the service schedule. Some services are only scheduled once or twice a year with appointments made months in advance of the service date. To avoid unnecessary scheduling or administrative delays in the calibration process, always make arrangements with the technical contact for the service you wish to utilize prior to shipping your instrument or artifact to us.

G. Customer Checklist

Please refer to last page of this chapter for a Customer Checklist which is intended to assist you in developing the basic information required to process an order for calibration services at NIST.

Customer Checklist for Ordering NIST Calibration Services

Information Obtained from NIST Technical Contact	Comments
NIST Contact (name/telephone)	Provide this information on your purchase order (PO)
Is the service available?	Please make sure customer's technical contact discusses service with NIST technical contact before proceeding.
NIST Service Identification Number	Provide this information on your PO
Estimated cost of services	Provide this information on your PO
Estimated turnaround time	Many calibration services are batched. Find out when to send the instrument.
Special instructions	
Packaging instructions	
Shipping instructions	
Other Precautions	
Information Supplied by the Customer on Purchase Order	
Purchase order number	
Purchase order date	
Customer's tax identification number	
Customer's mailing address	
Customer's billing address	
Name, telephone number, fax number, email address of administrative or procurement contact point at customer's location	
Name, telephone number, fax number, email address of technical contact point at customer's location	
Ship-to address (including NIST technical contact name)	
Return address (for shipment back to customer)	
NIST Service Identification Number	
Estimated cost	
Shipping terms (no FOB destination on return shipment)	
Special instructions from customer's technical contact	

CHAPTER 3

SPECIAL INSTRUCTIONS FOR FOREIGN CUSTOMERS

A. Foreign Inquires

Foreign customers should address all inquiries to:

PML Calibration Services
National Institute of Standards and Technology
100 Bureau Drive, Stop 8363
Gaithersburg, MD 20899-8363
United States of America
Telephone: (301) 975-2200
Fax: (301) 975-2950
Email: calibrations@nist.gov
Internet: www.nist.gov/calibrations/

NOTE: Please clearly indicate your **city** and **country** on all correspondence so that we may promptly respond to your request.

B. Criteria for Providing Service

Under certain circumstances, NIST is authorized to provide measurement service, including calibration services, for organizations or individuals located outside the United States. However, the Calibration Program must review each request for calibration services to determine if services are available to the requestor's organization in the requestor's country. Foreign customers must provide the following information, in writing, to the Calibration Program (see address above):

1. Identification of the item(s) to be calibrated, including serial and model numbers.
2. A detailed description of the measurements that are needed, or indicate the service identification number.
3. A description of any special requirement/circumstance that might affect the decision to provide the service. For example, will adjustments have to be made to the instrument, or will the time period be restricted in which the device is available for calibration?
4. A complete name and address of the requestor's organization.

C. Special Instructions

If the request for calibration service is accepted by NIST, the requesting organization will be notified of the cost of service and will be given the contact information for the NIST technical unit that will perform the measurements. The requesting organization must then complete the following steps:

1. Contact the NIST technical staff that will perform the service to determine the time schedule.
2. Send a purchase order to the Calibration Program. Provide complete addresses, including country, for returning the instrument and for mailing the calibration or test report.
3. NIST policy requires prepayment for all NIST calibration services requested by non-U.S. organizations. Before proceeding with any service(s), we will need a check, money order or a bank wire transfer. The prepayment must be for the full amount and be drawn on a U.S. bank. The prepayment methods are as follows:

Money Orders & Prepayment Checks

All foreign checks must be drawn on a United States Bank and made payable in US Dollars. All foreign checks must be mailed to the Receivables officer for deposit. In addition, please reference the NIST invoice/receivable number on the check stub. Checks made payable to the National Institute of Standards and Technology (NIST) should be mailed to:

NIST
Mail Stop 1624
100 Bureau Drive
Gaithersburg, MD 20899-1624

Prepayment by credit card

Please contact NIST Accounts Receivable Office at 301-975-3880, by email: billing@nist.gov, or by Fax: 301-975-8943.

Bank Wire Transfers

Payments may also be sent by wire using the US Department of Treasury FEDWIRE system and it can be done so to the following bank:

Treas NYC (Account is with the Federal Reserve Bank of New York)
U.S. Dept. of Treasury
33 Liberty Street
New York, NY 10045
Phone: 001-202-874-7132

In Payment Details field, CL329930001
ABA# 021030004
Account # 13060001
Account Name: TREAS NYC/CTR/BNF=/NIST/AC-13060001

Reference "Calibrations" to enable us to identify your payment. In addition, please be sure to pay any fees assessed for your bank wire transfers; otherwise, they will deduct it from your prepayment wire.

We cannot accept wire payment make through the Swift system only FEDWIRE. Therefore, we do not have a Swift code.

PLEASE NOTE: Our account number and name are of critical importance and must be referenced in order for NIST to be properly credited with your payment. It must appear in the precise manner shown to allow for the automated processing and classification of the funds transfer message. In addition, please refer to the NIST invoice number, your purchase order number, your country, and any other pertinent information that would help us identify you payment.

The transfer of funds can only be accomplished by your company going through a U.S. correspondent bank or by having your country's central bank send a swift telecommunication system message to the Federal Reserve Bank. **Be sure to cover any processing fees your bank may charge you.** Questions on bank wiring can be directed to the NIST Accounts Receivable Office at 301-975-3880, email: billing@nist.gov, or fax at 301-975-8943.

D. Shipping Charges

The calibration costs quoted ***do not*** include shipping, insurance, or the services of a customs broker. You must arrange and pay for these services separately. For your information, NIST currently uses the following customs brokers:

Gaithersburg, Maryland

Laing International
P.O. Box 16144
Washington, DC 20041
Phone: (703) 471-9279
Fax: (703) 471-8436

Boulder, Colorado

FedEx Trade Networks
4725 Paris Street, Suite 200
Denver, CO 80239
Phone: (303) 371-9550
Fax: (303) 373-0850

You are **not required** to use these customs brokers, but may select a broker of your choice.

CHAPTER 4

DIMENSIONAL MEASUREMENTS

A. Length Measurements

A.1 Gage Blocks

<u>Technical Contacts:</u>	<u>Telephone:</u>	<u>Email:</u>	<u>Mailing Address:</u>
Eric Stanfield (Long blocks)	(301) 975-4882	eric.stanfield@nist.gov	NIST
Beverly Connelly (Short blocks)	(301) 975-2485	beverly.connelly@nist.gov	100 Bureau Drive, Stop 8211
Theodore Doiron	(301) 975-3472	theodore.doiron@nist.gov	Gaithersburg, MD 20899-8211

Please contact the technical staff before shipping instruments or standards to the address listed above.

A.1 Gage Blocks		
Service ID Number	Description of Services	Fee (\$)
10010C	Gage Blocks: Set Up Charge, per order	190
10011C	Mechanical Comparisons, per Block (100 mm and shorter)	112
10012C	Mechanical Comparisons, per Block (over 100 mm)	272
10013C	Interferometry, per Block (100 mm and shorter), Maximum 25 Blocks per Order	318
10014C	Interferometry, per Block (over 100 mm)	At Cost
10015C	Non-standard size Gage Blocks	At Cost

Fees are subject to change without notice.

A.2 Line Standards

<u>Technical Contact:</u>	<u>Telephone:</u>	<u>Email:</u>	<u>Mailing Address:</u>
William B. Penzes	(301) 975-3477	wpenzes@nist.gov	NIST
Thomas W. LeBrun	(301) 975-4256	thomas.lebrun@nist.gov	100 Bureau Drive, Stop 8212
			Gaithersburg, MD 20899-8212

Please contact the technical staff before shipping instruments or standards to the address listed above.

A.2 Line Standards		
Service ID Number	Description of Service	Fee (\$)
10020C	Line Standards: Scales, < 1 m (40 inches), 4 Passes	9129
10021C	Line Standards: Scales, < 1 m (40 inches), 8 Passes	14073
10022C	Line Standards: Stage Micrometer, Per Scale, 30 Intervals, 2 Passes	1522
10023C	Line Standards: Stage Micrometer, Per Scale, 30 Intervals, 4 Passes	1902

10024C	Line Standards: End Standards, < 1 m	9320
10025C	Line Standards: Grid Plates, Less than 60 Intervals, 1 D Linear Calibration	15462

Fees are subject to change without notice.

A.3 Metal Tapes/Scales and Long Length Artifacts

<u>Technical Contact:</u>	<u>Telephone:</u>	<u>Email:</u>	<u>Mailing Address:</u>
Chris Blackburn	(301) 975-6413	chris.blackburn@nist.gov	NIST
Daniel S. Sawyer	(301) 975-5863	daniel.sawyer@nist.gov	100 Bureau Drive, Stop 8211 Gaithersburg, MD 20899-8211

Please contact the technical staff before shipping instruments or standards to the address listed above.

A.3 Metal Tapes/Scales and Long Length Artifacts		
Service ID Number	Description of Services	Fee (\$)
10030C	Metal Tapes: Surveying, Oil Gaging, and General Purpose; Metal Scales	At Cost
10040S	Special Tests of Long Length Artifacts	At Cost

A.4 Step Gages

<u>Technical Contacts:</u>	<u>Telephone:</u>	<u>Email:</u>	<u>Mailing Address:</u>
John Stoup	(301) 975-3476	john.stoup@nist.gov	NIST
Theodore Doiron	(301) 975-3472	theodore.doiron@nist.gov	100 Bureau Drive, Stop 8211 Gaithersburg, MD 20899-8211

Please contact the technical staff before shipping instruments or standards to the address listed above.

A.4 Step Gages		
Service ID Number	Description of Services	Fee (\$)
11060S	Special Tests of Step Gages	At Cost

A.5 Other Length Standards

Technical Contacts:

John Stoup
Theodore Doiron

Telephone:

(301) 975-3476
(301) 975-3472

Email:

john.stoup@nist.gov
theodore.doiron@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8211
Gaithersburg, MD 20899-8211

Please contact the technical staff before shipping instruments or standards to the address listed above.

A.5 Other Length Standards		
Service ID Number	Description of Services	Fee (\$)
10050S	Special Tests of Length Standards	At Cost

B. Diameter and Roundness Measurements

Technical Contacts:

Eric S. Stanfield
Theodore Doiron

Telephone:

(301) 975-4882
(301) 975-3472

Email:

eric.stanfield@nist.gov
theodore.doiron@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8211
Gaithersburg, MD 20899-8211

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
11010S	Special Tests of Cylindrical Diameter Standards (i.e. Plug and Pin Gages): Set Up Charge, per order	190
11011S	Mechanical comparison, per Gage (25 mm and smaller)	112
11012S	Interferometry, per Gage (50 mm and smaller)	259
11013S	Per Gage (over 50 mm)	At Cost
11014S	Roundness trace, per trace	212
11020C	Measuring Wires for Threads and Gears: Set Up Charge, per order	190
11021C	Single Wire, per wire	114
13020S	Special Tests of Roundness (Sphere and Hemisphere Types) Reversal Method: Radial Deviations from Best Fit Least-Squares Circle at 360 positions	1293
13030S	Special Tests of Roundness Calibration Specimens	At Cost
11030S	Special Tests of Spherical Diameter Standards; Balls: Set Up Charge, per order (applies to mechanical comparison and interferometry)	190
11031S	Mechanical Comparison (51 mm or smaller), Average Diameter, per ball, Expanded Uncertainty, $U \sim \pm 89$ nm to 115 nm	109
11032S	Mechanical Comparison (over 51 mm), Average Diameter, per ball	At Cost
11033S	Interferometry (25 mm or smaller) Average Diameter, per ball, Expanded	551

	Uncertainty, U ~ ± 30 nm	
11034S	Ball Out-of-Roundness: Least-Squares Out-of-Roundness and Polar Plots, price per trace (Typically three orthogonal traces for spheres and five traces for CMM calibration spheres) price per trace	105
Special Tests of Internal Diameter Standards: Ring Gages		
11040S	Plain Ring Gages, per ring	884
11050S	Special Tests of Diameter	At Cost

Fees are subject to change without notice.

C. Complex Dimensional Standards

C.1 API Threaded Plug and Ring Gages

Technical Contacts:

Dennis Everett
(12010C–12070S)

Eric Stanfield
(11050S)

John Stoup
(12060S)

Theodore Doiron

Telephone:

(301) 975-5272

(301) 975-4882

(301) 975-3476

(301) 975-3472

Email:

dennis.everett@nist.gov

eric.stanfield@nist.gov

john.stoup@nist.gov

theodore.doiron@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8211
Gaithersburg, MD 20899-8211

Please contact the technical staff before shipping instruments or standards to the address listed above.

C.1 API Threaded Plug and Ring Gages		
Service ID Number	Description of Services	Fee (\$)
12010C	Spec 5, 1.005 inches to 7 5/8 inches	2311
12011C	Spec 5, 8 5/8 inches to 20 inches	3509
12012C	Buttress Casing, 4 1/2 inches to 9 5/8 inches	2719
12013C	Buttress Casing, 10 inches to 13 3/8 inches	3289
12014C	Buttress Casing, 16 inches to 20 inches	3527
12015C	Line Pipe, 1/8 inch to 6 inches (New)	2238
12016C	Line Pipe, 8 inches to 20 inches (New)	2991
12017C	Extreme Line Casing, 5 inches to 7 inches (New)	3779
12018C	Extreme Line Casing, 5 inches to 7 inches (Used)	1421
12019C	Extreme Line Casing, 7 5/8 inches to 10 inches (New)	4323
12021C	Extreme Line Casing, 7 5/8 inches to 10 inches (Used)	1810
12022C	Spec 7 (Rotary), NC 23 - NC 61 (New)	2936
12023C	Spec 7 (Rotary), NC 70 (New)	3107
12024C	Spec 7 (Rotary), 1 inch to 4 1/2 inches, Reg. (New)	2931

12025C	Spec 7 (Rotary), 5 1/2 inches to 8 5/8 inches, Reg. (New)	3197
12026C	Spec 7 (Rotary), Any Type (Used)	1319
12027C	Spec 11B (Sucker Rods) P1, P2 Pin Go P7, P8 Pin Go B1, B2 Box Go (NEW)	1522/per set
12028C	Spec 11B (Sucker Rods) P1, P2 Pin Go P7, P8 Pin Go B1, B2 Box Go (USED)	766/per set
12029C	Spec 11B (Sucker Rods) P3, P4 Pin Cone B3, B4 Box Cone (NEW)	1806/per set
12031C	Spec 11B (Sucker Rods) P3, P4 Pin Cone B3, B4 Box Cone (USED)	699/per set
12032C	Spec 11B (Sucker Rods) P5, P6 Pin Cone B5, B6 Box Cone (NEW)	1188/per set
12033C	Spec 11B (Sucker Rods) P5, P6 Pin B5, B6 Box Cone (USED)	618/per set
12050S	Special Tests of Threaded Plug and Ring Gages	At Cost
12060S, 11050S	Special Tests of Two- and Three-Dimensional Gages	At Cost
12070S	Special Complex Dimensional Test, by Prearrangement	At Cost

Fees are subject to change without notice.

C.2 Sieves

Technical Contacts:

Theodore Doiron

Telephone:

(301) 975-3472

Email:

theodore.doiron@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8211
Gaithersburg, MD 20899-8211

Please contact the technical staff before shipping instruments or standards to the address listed above.

C.2 Sieves		
Service ID Number	Description of Services	Fee (\$)
10060S	Special Tests of Sieves	249

Fees are subject to change without notice.

C.3 Algorithms Testing and Evaluation Program for Coordinate Measuring Systems

Technical Contact:

Craig M. Shakarji

Telephone:

(301) 975-3545

Email:

shakarji@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8211
Gaithersburg, MD 20899-8211

Please contact the technical staff before shipping instruments or standards to the address listed above.

C.3 Algorithms Testing and Evaluation Program for Coordinate Measuring Systems		
Service ID Number	Description of Services	Fee (\$)
10070S	Special Test of CMS Software: NIST-generated data sets (basic service)	1944
10071S	Special Test of CMS Software: NIST-generated data sets (per geometry evaluated)	At Cost
10072S	Special Test of CMS Software: NIST-generated data sets, standard level (per geometry evaluated)	839
10080S	Special Test of CMS Software: Customer-generated data sets (basic service)	At Cost
10081S	Special Test of CMS Software: Customer-generated data sets (per geometry evaluated)	At Cost
10082S	Special Test of CMS Software: Customer-generated data sets, standard level (per geometry evaluated)	At Cost

Fees are subject to change without notice.

E. Optical Reference Planes and Roundness Standards

Technical Contacts:

Eric S. Stanfield
Theodore Doiron

Telephone:

(301) 975-4882
(301) 975-3472

Email:

eric.stanfield@nist.gov
theodore.doiron@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8211
Gaithersburg, MD 20899-8211

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
13010S	Special Tests of Optical Reference Planes (Flats): Optical Flat, ≤ 152 mm (6"), Per Surface	1580
13011S	Special Tests of Optical Reference Planes (Flats): Optical Flat, 152 mm to 203 mm (8")	2055
13012S	Special Tests of Optical Reference Planes (Flats): Optical Flat, 203 mm to 304 mm	2703
13013S	Special Tests of Optical Reference Planes (Flats): Optical Flat, ≥ 304 mm (12")	3378
13014S	Special Tests of Optical Reference Planes (Flats): Three Flat Calibration	At Cost

Fees are subject to change without notice.

F. Angular Measurements

Technical Contacts:

Bryon S. Faust
Theodore Doiron

Telephone:

(301) 975-4351
(301) 975-3472

Email:

bryon.faust@nist.gov
theodore.doiron@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8211
Gaithersburg, MD 20899-8211

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
14010C	Angle Gage Blocks: Set Up Charge, per order	190
14011C	Angle Gage Blocks, per block	183
14020S	Special Tests of Optical Polygons	At Cost
14030S	Special Tests of Rotary and Indexing Tables: Every 30°	2581
14031S	Special Tests of Rotary and Indexing Tables: (30°, 5°, 1°) Calibration	5149
14040S	Special Tests of Optical Wedges: Fixed-Angle Wedge	887
14041S	Special Tests of Optical Wedges: Variable-Angle Wedge	At Cost
14050S	Special Angular Measurements, by Prearrangement	At Cost

Fees are subject to change without notice.

G. Laser Measurements

Technical Contact:

Jack Stone

Telephone:

(301) 975-5638

Email:

jack.stone@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8211
Gaithersburg, MD 20899-8211

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
14510S	Laser Frequency/Wavelength, Full Calibration	2853
14511S	Quick Check of Frequency/Wavelength at Laboratory Conditions	1483

Fees are subject to change without notice.

H. Surface Texture

Technical Contact:

T. Brian Renegar

Telephone:

(301) 975-4274

Email:

brenegar@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8212
Gaithersburg, MD 20899-8212

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
15010C	Roughness Calibration Specimens	1686
15030C	Step Height Measurements	1686
15040S	Surface Roughness and Topography Special Tests	At Cost

Fees are subject to change without notice.

CHAPTER 5

MECHANICAL MEASUREMENTS

A. Hydrometers

Technical Contacts:

Sherry Sheckels
John D. Wright

Telephone:

(301) 975-5940
(301) 975-5937

Email:

sherry.sheckels@nist.gov
john.wright@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8361
Gaithersburg, MD 20899-8361

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
16010C	Reference Standard Hydrometers	1303
16020S	Hydrometers Special Tests	At Cost

Fees are subject to change without notice.

B. Volume and Density

Technical Contacts:

Sherry Sheckels
John D. Wright

Telephone:

(301) 975-5940
(301) 975-5937

Email:

sherry.sheckels@nist.gov
john.wright@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8361
Gaithersburg, MD 20899-8361

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
17010C	Volume Standards < 380 L	2144
17020C	Volume Standards > 380 L, 2 points	2956
17030C	Volume Standards > 380 L, 5 points	4176
17040S	Volume Special Tests	At Cost

Fees are subject to change without notice.

C. Flow Measurements

Technical Contacts:

Gina Kline
(Gas Flow)

John D. Wright
(Gas Flow)

Iosif Shinder
(Water Flow)

Aaron Johnson
(Gas Flow and Hydrocarbon Flow)

Sherry Sheckels
(Hydrocarbon Flow)

Telephone:

(301) 975-4813

(301) 975-5937

(301) 975-5943

(301) 975-5954

(301) 975-5940

Email

gina.kline@nist.gov

john.wright@nist.gov

iosif.shinder@nist.gov

aaron.johnson@nist.gov

sherry.sheckels@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8361
Gaithersburg, MD 20899-8361

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
18010C	Gas Flow Meters	4637
18015C	Natural Gas Flow Calibration	At Cost
18020C	Water Flow Meters	4454
18040C	Transfer Standards	At Cost
18050S	Gas Flow Special Tests	At Cost
18060S	Water Flow Special Tests	At Cost
18070S	Hydrocarbon Liquid Flow Special Tests	At Cost

Fees are subject to change without notice.

See 30063S Special Tests for Low-Gas-Flow Instrumentation

D. Flow Measurements at Cryogenic Temperatures

Technical Contact:

Michael Lewis

Fax: (303) 497-5224

Telephone:

(303) 497-3458

Email

mlewis@boulder.nist.gov

Mailing Address:

NIST
325 Broadway, MC 838.09
Boulder, CO 80305-3328

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
18800S	Special Tests of Cryogenic Liquid Flow	At Cost

E. Air Speed Measurements

Technical Contacts:

Iosif Shinder

Telephone:

(301) 975-5943

Email:

iosif.shinder@nist.gov

Mailing Address:NIST
100 Bureau Drive, Stop 8361
Gaithersburg, MD 20899-8361

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
19010C	High Air Speed Instruments 1.3 m/s to 67 m/s (3 mph to 150 mph)	2697
19030S	High Air Speed Special Tests	At Cost

Fees are subject to change without notice.

F. Mass Standards

Technical Contacts:

Patrick Abbott

Zeina J. Kubarych

Telephone:

(301) 975-4218

(301) 975-4468

Email:patrick.abbott@nist.govzeina.kubarych@nist.gov**Mailing Address:**NIST
100 Bureau Drive, Stop 8221
Gaithersburg, MD 20899-8221**Administrative and Logistics:**

June Eckley

(301) 975-5866

june.eckley@nist.gov**Fax:** (301) 417-0514

IMPORTANT NOTES TO OUR CUSTOMERS:

1. Please contact the technical staff for correct Fee and appropriate Service ID Number for your equipment.
2. Please do not send purchase orders and equipment to NIST without scheduling a calibration.
3. Calibrations for variations of complete standard weight sets are available. These may require fewer (or more) than the number of measurement series required for the calibration of a complete standard weight set. These variations will affect pricing of the service. Contact the technical staff for details.
4. If you request a calibration estimate (which includes cost and turnaround time estimates and start date of calibration), please note that we need to receive a confirmation from you to reserve the calibration start date. If no confirmation is received within 30 days, the reservation will be cancelled and the start date given to the next customer.

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
22011C	Weight cleaning	304
22021C	Single or two equal weights 1 kg or 100 g	2843
22022C	Three equal weights 1 kg or 100 g	4069
22023C	Combination of 5,2,2,1 in the range of 1 kg - 1 mg	2843
22031C	Combination of 5,2,2,1 in the range of 2 kg to 5 kg	2859

22032C	Single or two equal weights 10 kg to 50 kg	2859
22110S	Single Weights > 50 kg to 1200 kg	At Cost
22120S	Single Weights 1200 kg to 28000 kg	At Cost
22160C	Single Weights for Dead Weight Pressure Testers < 10 kg	1141
22140C	Single Weights for Dead Weight Pressure Testers > 22.7 kg (> 50 lb)	At Cost
22161C	Single Weights for Dead Weight Pressure Testers > 10 kg to 50 kg	1455
22170S	Special Mass Measurement Services	At Cost

Fees are subject to change without notice.

G. Force Measurements

Technical Contacts:

Rick L. Seifarth

Samuel L. Ho

Kevin L. Chesnutwood

Telephone:

(301) 975-6652

(301) 975-6648

(301) 975-6653

Email:

ricky.seifarth@nist.gov

samuel.ho@nist.gov

kchesnut@nist.gov

Mailing Address:

NIST

100 Bureau Drive, Stop 8222

Gaithersburg, MD 20899-8222

Administrative and Logistics:

June Eckley

(301) 975-5866

june.eckley@nist.gov

Fax: (301) 417-0514

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
23010C	Force Transducers to 112 540 N (25 300 lbf) 1 mode	3603
23020C	Extra observation	72
23030C	Additional bridges	973
23040C	Force Transducers to 112 540 N (25 300 lbf) 2 modes	5973
23050C	Extra observation	72
23060C	Additional bridges	983
23070C	Force Transducers 112 540 N to 498 201 N (25 300 lbf to 112 000 lbf) 1 mode	4137
23080C	Extra observation	72
23090C	Additional bridges	1116
23100C	Force Transducers 112 540 N to 498 201 N (25 300 lbf to 112 000 lbf) 2 modes	8142
23110C	Extra observation	213
23120C	Additional bridges	2259
23130C	Force Transducers 498 205 N to 1 334 467 N (112 000 lbf to 300 000 lbf) 1 mode	8475

23140C	Extra observation	213
23150C	Additional bridges	1404
23160C	Force Transducers 498 205 N to 1 334 467 N (112 000 lbf to 300 000 lbf) 2 modes	13511
23170C	Extra observation	292
23180C	Additional bridges	2526
23190C	Force Transducers 1 334 471 N to 4 448 222 N (300 00 lbf to 1 000 000 lbf) 1 mode	10133
23200C	Extra observation	213
23210C	Additional bridges	1967

23220C	Force Transducers 1 334 471 N to 4 448 222 N (300 00 lbf to 1 000 000 lbf) 2 modes	15988
23230C	Extra observation	279
23240C	Additional bridges	3522
23250C	Force Transducers over 4 448 222 N (1 000 000 lbf) compression only	At Cost
23260S	Special Tests of Force Transducers	At Cost

Fees are subject to change without notice.

H. Vibration Measurements

Technical Contacts:

Janet M. Cassard

Telephone:

(301) 975-2049

Email:

janet.cassard@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8220
Gaithersburg, MD 20899-8220

Administrative and Logistics:

Beverly Connelly (301) 975-2485

beverly.connelly@nist.gov

Fax: (301) 990-8291

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Freq. Range	Peak Accel.	Fee (\$)
24010C	Transducer Sensitivity	2 Hz to 160 Hz	0.2 g _n to 1 g _n	3311
24020C	Transducer Sensitivity	10 Hz to 3500 Hz	2 g _n to 10 g _n	5773
24030C	Transducer Sensitivity	10 Hz to 10 kHz	2 g _n to 10 g _n	8199
24040S	Shock Measurement	250 Hz to 10 kHz	20 g _n to 10 000 g _n	At Cost
24050S	Transducer Sensitivity	3 kHz to 20 kHz	4 g _n to 200 g _n	At Cost
24060S	Special Vibration Tests, by Prearrangement			At Cost

Fees are subject to change without notice.

I. Acoustic Measurements

Technical Contacts:

Randall P. Wagner

Telephone:

(301) 975-6619

Email:

randall.wagner@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8221
Gaithersburg, MD 20899-8221

Administrative and Logistics:

Beverly Connelly

(301) 975-2485

beverly.connelly@nist.gov

Fax: (301) 990-8291

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
25010C	Pressure Response: WE Type 640AA microphones or equivalent (e.g., Tokyo Riko Type ECL MR103; Bruel & Kjaer Type 4160, Bruel & Kjaer Types 4144 or 4132 with DB0111 adapter), 50 Hz to 10 000 Hz	6465
25020C	Pressure Response: WE Type 640AA microphones or equivalent (e.g., Tokyo Riko Type ECL MR103; Bruel & Kjaer Type 4160; Bruel & Kjaer Types 4144 or 4132 with DB0111 adapter), 50 Hz to 20 000 Hz	7797
25030C	Pressure Response: Tokyo Riko Type ECL MR112, Bruel & Kjaer Type 4134, or equivalent half-inch microphones, 50 Hz to 10 000 Hz	7531
25040C	Pressure Response: Tokyo Riko Type EC MR112, Bruel & Kjaer Type 4134, or equivalent half-inch microphones, 50 Hz to 20 000 Hz	9510
25050C	Free-Field Response: Tokyo Riko Type ECL MR112, Bruel & Kjaer Types 4133, 4134, 4165, 4166, 4180, or equivalent half-inch microphones, 2500 Hz to 20 000 Hz	7033
25060S	Special Tests of Acoustic Devices	At Cost
25070S	Special Tests of Audiometers/Earphones	6033

Fees are subject to change without notice.

CHAPTER 6

THERMODYNAMIC QUANTITIES

A. Pressure Measurements

<u>Technical Contacts:</u>	<u>Telephone:</u>	<u>Email:</u>	<u>Mailing Address:</u>
Douglas A. Olson (All Services)	(301) 975-2956	dolson@nist.gov	NIST
R. Gregory Driver (Pneumatic gages) (29010C, 29030C, 29035C, 29040S)	(301) 975-4832	rdriver@nist.gov	100 Bureau Drive, Stop 8364 Gaithersburg, MD 20899-8364

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
29010C	Deadweight Piston Gages	5005
29020C	Controlled Clearance Piston Gages	At Cost
29030C	Pressure Gages and Transducers	At Cost
29035C	Non-mercurial Barometers and Manometers	At Cost
29040S	Special Tests of Pressure Gages	At Cost

Fees are subject to change without notice.

B. Vacuum, Low Pressure and Leak Measurements

<u>Technical Contacts:</u>	<u>Telephone:</u>	<u>Email:</u>	<u>Mailing Address:</u>
Jacob Ricker (30005C) (30010C–30025C, 30040S)	(301) 975-4475	jacob.ricker@nist.gov	NIST
Jay H. Hendricks (30005C–30025C, 30040S)	(301) 975-4836	jay.hendricks@nist.gov	100 Bureau Drive, Stop 8364 Gaithersburg, MD 20899-8364
James A. Fedchak (30029C–30032S, 30034C–30038C, 30050S)	(301) 975-8962	james.fedchak@nist.gov	
R. Gregory Driver (30060S–30063S, 30062C)	(301) 975-4832	rdriver@nist.gov	

Please contact the technical staff before shipping instruments or standards to the address listed above.

NOTE: 1 Torr = 133.322 Pa

Service ID Number	Description of Services	Fee (\$)
30005C	Vacuum, Comparison Calibration	845
30010C	One Low-Pressure Transducer Absolute or Differential Relative to Vacuum	3099
30011C	Additional Transducer (Cost per Unit)	2917
30020C	One Differential Low-Pressure Transducer Relative to near Atmospheric Pressure	5554

30021C	Additional Transducers (Cost per Unit)	5070
30025C	Piston Gauges versus an Ultrasonic Interferometer Manometer	At Cost
30029C	Spinning Rotor Gages, below 0.1 Pa, Nitrogen Gas with NIST Controller	3636
30030C	Spinning Rotor Gages, below 0.1 Pa, Nitrogen Gas Customer Controller with IEEE-488	3636
30031C	Spinning Rotor Gages, below 0.1 Pa, Additional Gas	4398
30032S	Special Test of Spinning Rotor Gages, Transition Range (above 0.1 Pa)	At Cost
30034C	Ionization Gages, 10^{-4} Pa to 10^{-1} Pa, Nitrogen Gas	4366
30035C	Ionization Gages, 10^{-5} Pa to 10^{-1} Pa, Nitrogen Gas	5360
30036C	Ionization Gages, 10^{-7} Pa to 10^{-1} Pa, Nitrogen Gas	5672
30037C	Ionization Gages, Additional Filament or Gas for Above Tests	At Cost
30038C	Ionization Gages, NIST Supplied Gage Tube for Above Tests	333
30040S	Special Tests of Low-Pressure Gages	At Cost
30050S	Special Tests of Vacuum Gages	At Cost
30060S	Special Tests of Leak Artifacts (10^{-13} mol/s to 10^{-6} mol/s)	At Cost
30061C	Helium Leaks, Primary Calibration (10^{-13} mol/s to 10^{-6} mol/s)	3189
30062C	Helium Leaks, Comparison Calibration (10^{-13} mol/s to 10^{-9} mol/s)	2425
30063S	Special Tests of Low-Gas-Flow Instruments	At Cost

Fees are subject to change without notice.

NOTE: Due to the time and effort required preparing vacuum instrumentation for calibration it is particularly important that they be known to be in proper operating condition when they are submitted to NIST. Equipment will be inspected upon receipt and the customer notified of any obvious damage. If the schedule permits, we will cooperate with the customer's efforts to repair or replace damaged equipment so that the calibration of their equipment can proceed. However, concealed damage or operational deficiencies most likely will not be detected before the instrument is operating on the vacuum system or the calibration has started; in such cases, **if the equipment cannot be calibrated, we will charge 20 % of the regular calibration fee for low-pressure transducers and 30 % of the regular fee for spinning rotor and ionization gages.**

C. Laboratory and Industrial-Grade Thermometers

Technical Contact:

C. Dawn Cross

Telephone:

(301) 975-4822

Email:

dawn.cross@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8363
Gaithersburg, MD 20899-8363

Please contact the technical staff before shipping instruments or standards to the address listed above.

NOTE: NIST no longer calibrates mercury in glass thermometers as of March 1, 2011. Fahrenheit ranges are not direct conversions of the Celsius ranges.

Service ID Number	Description of Services	Fee (\$)
31010C	Organic Liquid in Glass Thermometers (0 °C to 200 °C) (32 °F to 392 °F)	255/pt
31040C	Organic Liquid in Glass Thermometers (−1 °C to −110 °C) (31 °F to −166 °F)	357/pt
31050C	Organic Liquid in Glass Thermometers (Liquid N ₂) (−196 °C or −321 °F)	255/pt
31100C	Quantity Tests of Liquid-In-Glass Thermometers	150
31110C	Special Tests of Industrial Platinum Resistance Thermometers, Thermistor Thermometers, Digital Thermometers and Other Types of Thermometers (0 °C to 150 °C) (32 °F to 300 °F)	150/pt
31120C	Special Tests of Industrial Platinum Resistance Thermometers, Thermistor Thermometers, Digital Thermometers and Other Types of Thermometers (151 °C to 315 °C) (301 °F to 600 °F)	150/pt
31130C	Special Tests of Industrial Platinum Resistance Thermometers, Thermistor Thermometers, Digital Thermometers and Other Types of Thermometers (316 °C to 550 °C) (601 °F to 1022 °F)	150/pt
31140C	Special Tests of Industrial Platinum Resistance Thermometer, Thermistor Thermometers, Digital Thermometers and Other Types of Thermometers (−1 °C to −110 °C) (31 °F to −166 °F)	150/pt
31150C	Special Tests of Industrial Platinum Resistance Thermometers, Thermistor Thermometers, Digital Thermometers and Other Types of Thermometers (Liquid N ₂) (−196 °C or −321 °F)	180/pt
31190S	Additional copy of Table from Results of 31110S–31150S at a Later Date	265
31200S	Preliminary Examination of Ineligible Thermometer	109
31260S	Special Thermometry Services, by Prearrangement	At Cost

Fees are subject to change without notice.

D. Thermocouples, Thermocouple Materials, Thermometer Indicators

Technical Contacts:

Karen Garrity
(32010C–32101C)
C. Dawn Cross
(32110C–32120C)

Telephone:

(301) 975-4818

(301) 975-4822

Email:

kgarrity@nist.gov

dawn.cross@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8363
Gaithersburg, MD 20899-8363

Please contact the technical staff before shipping instruments or standards to the address listed above.

Comparison Calibrations, Temperature Measured with Thermocouple (TC)						
Service ID Number	TC Type	Temp Range °C	Points	Min. Length (mm)	Temp. (°C)	Fee (\$)
32010C	S	0 to 1450	1 °C or 1 °F Interv. Table	700	0 to 1100 1450	771
32020C	R	0 to 1450	1 °C or 1 °F Interv. Table	700	0 to 1100 1450	771
32030C	B	0 to 1750	1 °C or 1 °F Interv. Table	1000	0 to 800 800 to 1100 1450 1750	1159
32031C	B	800 to 1750	1 °C or 1 °F Interv. Table	1000	800 to 1100 1450 1750	771
32040C	E	0 to 1000	4 to 15	700	0 to 1000	771
32041C	J	0 to 760	4 to 15	700	0 to 760	771
32042C	K	0 to 1100	4 to 15	700	0 to 1100	771
32043C	N	0 to 1100	4 to 15	700	0 to 1100	771
32044C	T	0 to 400	4 to 15	700	0 to 400	771
32050C	Comparison calibration, two point minimum, per point, for all items above					359/pt
32060C	Each additional table of results at 1 °C or 1 °F intervals, for type S, R, or B at later date					284
32070C	Thermocouple materials tested against Pt Thermoelectric standard, 4 to 15 points, 700 mm minimum lengths					995

Calibration at Metal Freezing Points, Minimum TC Wire Diameter 0.4 mm, Freezing Point Determination at Au, Ag, Al, and Zn						
Service ID Number	TC Type	Temp Range °C	Points	Min. Length (mm)	Temp. (°C)	Fee (\$)
32090C	S or R	0 to 1450	Table 1 °C or 1 °F Interv. and equations to generate table	1000	at freezing points 0 to 1100 1450	1751
32091C	Type S or T, freezing point determination, per point, two point minimum					551
Calibration of Digital Thermometer Indicator or Portable Potentiometer						
32100C	Indicator or Potentiometer, first dial or range					1119
32101C	Indicator or Potentiometer, each additional dial or range					635
Comparison Calibration of Thermocouples or Thermocouple Materials Tested against Pt Thermoelectric Standard, Temperature Measured with Standard Platinum Resistance Thermometer, Minimum TC Wire Length 1.0 m, 2 Point Minimum						
32110C	Range –110 °C to 315 °C and Liquid N ₂ (–196 °C) or –166 °F to 600 °F and Liquid N ₂ (–321 °F), Expanded Uncertainty 0.4 °C					405/pt
32120C	316 °C to 550 °C or 601 °F to 1022 °F, Expanded Uncertainty 0.5 °C					505/pt
Table at one degree intervals for Type T thermocouple for any of the following options: (The cost of the table will be in addition to the calibration per point covered under fee schedule services numbered 32110C–32120C).						

Fees are subject to change without notice.

NOTE: Due to the extra time involved in calibrating sheathed thermocouples, a surcharge of 20 % of the cost of calibrating bare-wire thermocouples will be added to the relevant fees listed above.

E. Resistance Thermometry

Technical Contacts:

Weston L. Tew
(0.65 K to 84 K)
Michal J. Chojnacky
(83 K to 962 °C)

Telephone:

(301) 975-4811
(301) 975-4821

Email:

wtew@nist.gov
michalc@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8363
Gaithersburg, MD 20899-8363

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
33010C	Capsule SPRT (13.8 K to 30 °C) e-H ₂ to Ga	10021
33020C	Capsule SPRT (13.8 K to 157 °C) e-H ₂ to In	10430
33030C	Capsule SPRT (13.8 K to 232 °C) e-H ₂ to Sn	10839
33031C	Capsule SPRT (24.5 K to 30 °C) Ne to Ga	7451

33032C	Capsule SPRT (24.5 K to 157 °C) Ne to In	7859
33033C	Capsule SPRT (24.5 K to 232 °C) Ne to Sn	8270
33040C	Capsule SPRT(54 K to 30 °C) O ₂ to Ga	6460
33050C	Capsule SPRT (54 K to 157 °C) O ₂ to In	6869
33060S	Capsule SPRT (54 K to 232 °C) O ₂ to Sn	7278
33065S	Capsule SPRT (83 K to 0.01 °C) Ar to TPW	At Cost
33070C	Capsule SPRT (83 K to 30 °C) Ar to Ga	3507
33080C	Capsule SPRT (83 K to 157 °C) Ar to In	3711
33090C	Capsule SPRT (83 K to 232 °C) Ar to Sn	4068
33100C	Capsule SPRT (0 °C to 30 °C) TPW to Ga	1419
33110C	Capsule SPRT (0 °C to 157 °C) TPW to In	2084
33120C	Capsule SPRT (0 °C to 232 °C) TPW to Sn	2677
33130C	Capsule SPRT (234 K to 30 °C) Hg to Ga	2687
33140C	Rhodium-Iron or Platinum-Cobalt Resistance Thermometers (0.65 K to 24.6 K)	11759
33141C	Rhodium-Iron or Platinum-Cobalt Resistance Thermometers (0.65 K to 83.8 K)	14077
33142C	n-Type Germanium Resistance Thermometers (0.65 K to 24.6 K)	11325
33150C	Long Stem SPRT (83 K to 0.01 °C) Ar to TPW	2811
33160C	Long Stem SPRT (83 K to 30 °C) Ar to Ga	3220
33170C	Long Stem SPRT (83 K to 157 °C) Ar to In	3414
33180C	Long Stem SPRT (83 K to 232 °C) Ar to Sn	3741
33190C	Long Stem SPRT (83 K to 420 °C) Ar to Zn	4304
33200C	Long Stem SPRT (83 K to 661 °C) Ar to Al	5501
33210C	Long Stem SPRT (234 K to 30 °C) Hg to Ga	2380
33220C	Long Stem SPRT (234 K to 157 °C) Hg to In	3096
33230C	Long Stem SPRT (234 K to 232 °C) Hg to Sn	3455
33240C	Long Stem SPRT (234 K to 420 °C) Hg to Zn	3894
33250C	Long Stem SPRT (234 K to 661 °C) Hg to Al	4529
33260C	Long Stem SPRT (0 °C to 30 °C) TPW to Ga	1122
33270C	Long Stem SPRT (0 °C to 157 °C) TPW to In	1745
33280C	Long Stem SPRT (0 °C to 232 °C) TPW to Sn	2359
33290C	Long Stem SPRT (0 °C to 420 °C) TPW to Zn	2819

33300C	Long Stem SPRT (0 °C to 661 °C) TPW to Al	3433
33310C	Long Stem SPRT (0 °C to 962 °C) TPW to Ag	6788
33330C	Additional Copy of Table from Results of 33010C–33310C at a Later Date	242
33340C	Minimum Charge for Unsuitable Thermometer	1060
33350S	Special Tests of Resistance Thermometers	At Cost
33355S	Special Tests of Cryogenic Resistance Thermometers	At Cost
33360S	Special Tests of Thermometric Fixed-Point Devices	At Cost
33370M	Measurement Assurance Program for Temperature 83 K to 420 °C (Ar to Zn)	12791
33380M	Measurement Assurance Program for Temperature 83 K to 661 °C (Ar to Al)	16289

Fees are subject to change without notice.

F. Radiance Temperature Measurements

Technical Contact:

Charles E. Gibson

Telephone:

(301) 975-2329

Email:

cgibson@nist.gov

Mailing Address:

NIST

100 Bureau Drive, Stop 8441

Gaithersburg, MD 20899-8441

Fax: (301) 869-5700

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
Calibration reports are issued giving the radiance temperature of the blackbody at 655.48 nm versus the scale reading, output current, or output voltage		
35010C	Radiance Temperature Standard, Disappearing Filament Optical Pyrometer (800 °C to 2400 °C, 4 to 12 points, 1 range)	8435
35020C	Radiance Temperature Standard, Disappearing Filament Optical Pyrometers (each additional range up to 4200 °C, only available with 35010C)	6123
35040C	Radiance Temperature Standard, Disappearing Filament Optical Pyrometer (800 °C to 4200 °C, 1 range, 3 or fewer points)	4196
Calibration reports are issued giving the radiance temperature of the lamp at 655.48 nm versus the lamp current		
35050C	Radiance Temperature Standard, Tungsten Strip Lamp (800 °C to 2300 °C, 6 to 16 points)	11905
35051C	Recalibration of Tungsten Strip Lamp (800 °C to 2300 °C, 6 to 16 points)	9978
35060C	Radiance Temperature Standard, Tungsten Strip Lamp (800 °C to 2300 °C, 5 or fewer points)	7665
35061C	Recalibration of Tungsten Strip Lamp (800 °C to 2300 °C, 5 or fewer points)	5737
Calibration reports are issued giving the radiance temperature of the reference blackbody at 655.48 nm, 900 nm or 1000 nm versus the display reading, output current, or output voltage		

35070S	Special Tests of Radiation Thermometers (800 °C to 2700 °C)	At Cost
35071C	Radiance Temperature Standard, Radiation Thermometer (800 °C to 2700 °C, 6 to 20 points)	9206
35072C	Radiance Temperature Standard, Radiation Thermometer (800 °C to 2700 °C, 5 or fewer points)	4581
Calibration reports are issued giving the thermodynamic temperature of the reference blackbody versus the radiation thermometer display reading, output current, or output voltage.		
35080S	Special Tests of Radiation Thermometers (-46 °C to 900 °C)	At Cost
35085C	Radiance Temperature Standard, Radiation Thermometer (-46 °C to 900 °C, 3 points)	4902
35086C	Radiance Temperature Standard, Radiation Thermometer (-46 °C to 900 °C, Each additional point when ordered with 35085C)	963/point
Calibration reports are issued giving the thermodynamic temperature of the reference blackbody versus the test blackbody source display reading.		
35090S	Special Tests of Blackbody Sources (-46 °C to 900 °C)	At Cost
Calibration reports are issued giving heat flux at the sensor surface versus the output voltage.		
35100S	Special Tests of Radiative Heat Flux Sensors	At Cost
35101C	Radiative Heat Flux Sensors (1 W/cm ² to 5 W/cm ² , 9 points, Gardon and Schmidt-Boelter type sensors)	3424
35102C	Additional Radiative Heat Flux Sensor (same model as 35101C)	2654

Fees are subject to change without notice.

Calibration Schedule: Requests for calibration services are scheduled after receipt of a purchase order.

G. Humidity Measurements

Technical Contacts:

Christopher Meyer

Gregory E. Scace

Telephone:

(301) 975-4825

(301) 975-2626

(301) 975-2626

Email

cmeyer@nist.gov

gregory.scace@nist.gov

Mailing Address:

NIST

100 Bureau Drive, Stop 8363

Gaithersburg, MD 20899-8363

Fax: (301) 548-0206

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
36010C	Dew-Point Hygrometers (Dew/Frost point only) Range: -70 °C to 85 °C	207/point
36020C	Relative Humidity Hygrometers (RH sensors and psychrometers), Range: 3% to 98% at temperatures from 5 °C to 85 °C	207/point
36030C	External Temperature Probe for Dew-point Hygrometer (enabling RH measurements) Range: -110 °C to 150 °C	376/point
36040C	Electrolytic Hygrometers	At Cost

36070S	Special Tests of Humidity	At Cost
--------	---------------------------	---------

Fees are subject to change without notice.

H. Thermal Resistance Measurements

Technical Contact:

Robert Zarr

Telephone:

(301) 975-6436

Email:

robert.zarr@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8632
Gaithersburg, MD 20899-8632
Fax: (301) 975-5433

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Material	Specimen Thickness (mm)	Mean Temp. (K)	Temp. Difference (K)	Relative Expanded Uncertainty $k = 2$ (%)	Fee (\$)
36110C	Fibrous glass blanket	25	297	22 or 28	1.0	2690/pt
36120C	Fibrous glass blanket	75	297	22 or 28	1.5	2690/pt
36130C	Fibrous glass blanket	150	297	22 or 28	2.5	2690/pt
36140C	Fibrous glass blanket	225	297	22 or 28	3.0	2690/pt
36150C	Quantity Tests of Fibrous glass blanket		297	22 or 28		At Cost
36199S	Special Tests of Thermal Insulation		280 to 330	22 or 28		At Cost

Fees are subject to change without notice.

CHAPTER 7

OPTICAL RADIATION MEASUREMENTS

A. Photometric Measurements

Technical Contact:

Yuqin Zong

Telephone:

(301) 975-2332

Email:

yuqin.zong@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8442
Gaithersburg, MD 20899-8442
Fax: (301) 840-8551

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
37010C	Luminous Intensity and Color Temperature Standard Lamps	4408
37020S	Special Tests for luminous Intensity and Color Temperature of Submitted Lamps	At Cost
37030C	Color Temperature Standard Lamps	3637
37040C	Each Additional Color Temperature for 37030C	579
37050S	Special Tests for Color Temperature of Submitted Lamps	At Cost
37060S	Special Tests for Total Luminous Flux of Submitted Incandescent Lamps and Florescent Lamps	At Cost
37070C	Opal Glass Luminance Coefficient Standards	3003
37080S	Special Tests for Submitted Luminance Sources and Transmitting Diffusers	At Cost
37090S	Special Tests for Photometers, Illuminance Meters and Luminance Meters	At Cost
37100S	Special Photometric Tests	At Cost
37110S	Special Tests for Submitted Flashing-Light Photometers	At Cost
37120S	Special Tests for Color Measuring Instruments for Displays	At Cost
37130S	Special Tests for Luminous Intensity and Luminous Flux of LEDs	At Cost

Fees are subject to change without notice.

B. Ozone Measurements

Technical Contacts:

James Norris

Telephone:

(301) 975-3936

Email:

james.norris@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8393
Gaithersburg, MD 20899-8393

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
37510C	Ozone Instrument Calibrations	1905
37515S	Additional Special Tests for Ozone Instruments	At Cost
37520C	NIST Standard Reference Photometer (NIST SRP)	87937
37525S	NIST Standard Reference Photometer Maintenance	At Cost
37530C	Validation of NIST Standard Reference Photometer (NIST SRP)	4139
37535S	Additional Special Tests for Validation of NIST Standard Reference Photometer (NIST SRP)	At Cost

Fees are subject to change without notice.

C. Optical Properties of Materials Measurements

Technical Contacts:

Catherine Cooksey
(38010C-38061S,
38075S)
Melody Smith
(38065C-38069C)

Telephone:

(301) 975-6208

Email:

catherine.cooksey@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8442
Gaithersburg, MD 20899-8442
Fax: (301) 840-8551

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
38010C	Spectral Transmittance Filters (Cobalt Blue Glass)	2838
38020C	Spectral Transmittance Filters (Copper Green Glass)	2838
38030C	Spectral Transmittance Filters (Carbon Yellow Glass)	2838
38040C	Spectral Transmittance Filters (Selenium Orange Glass)	2838
38060S	Special Tests of Spectral Reflectance (250 nm to 2500 nm)	At Cost
38061S	Special Tests of Spectral Transmittance and Index of Refraction (120 nm to 2500 nm)	At Cost
38065C	Recertification of NIST photometric Standard Reference Materials SRM 930, SRM 1930, or SRM 2930	1333
38066C	Recertification of NIST photometric Standard Reference Material SRM 2031	1866

38067C	Recertification of NIST photometric Standard Reference Material SRM 2030	906
38068C	Replacement filter for NIST photometric Standard Reference Materials SRM 930, SRM 1930, SRM 2030 or SRM 2930	860
38069C	Replacement filter for NIST photometric Standard Reference Material SRM 2031	1289
38075S	Special Tests Infrared Reflectance, Transmittance, and Emittance of Materials	At Cost

Fees are subject to change without notice.

D. Surface Color and Appearance

<u>Technical Contacts:</u>	<u>Telephone:</u>	<u>Email:</u>	<u>Mailing Address:</u>
Maria E. Nadal (38090S and 38091S)	(301) 975-4632	maria.nadal@nist.gov	NIST 100 Bureau Drive, Stop 8442 Gaithersburg, MD 20899-8442
Martin Wilson (38100C–38130C)	(301) 975-2356	martin.wilson@nist.gov	Fax: (301) 840-8551

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
38090S	Specular Gloss	At Cost
38091S	Special Test of 0°/45° Surface Color	At Cost
38100C	X-Ray Film Step Tablet Transmission Density Standard (Replacement for SRM 1001)	771
38110C	Recalibration of an X-Ray Film Step Tablet Transmission Density Standard	1117
38120C	Photographic Film Step Tablet Transmission Density Standard (Replacement for SRM 1008)	945
38130C	Recalibration of a Photographic Film Step Tablet Transmission Density Standard	1271

Fees are subject to change without notice.

E. Spectroradiometric Measurements

E.1 Spectroradiometric Source Measurements

<u>Technical Contacts:</u>	<u>Telephone:</u>	<u>Email:</u>	<u>Mailing/Shipping Address:</u>
Charles E. Gibson (39010C–39060S)	(301) 975-2329	cgibson@nist.gov	NIST 100 Bureau Drive, Stop 8441 Gaithersburg, MD 20899-8441
Jeanne M. Houston (39071C–39081S)	(301) 975-2327	jeanne.houston@nist.gov	Fax: (301) 869-5700
Thomas C. Larason (39080S, 39081S, 39100S)	(301) 975-2334	tlarason@nist.gov	
George Eppeldauer (39090S)	(301) 975-2338	geppeldauer@nist.gov	

Please contact the technical staff before shipping instruments or standards to the address listed above.

E.1 Spectroradiometric Source Measurements		
Service ID Number	Description of Services	Fee (\$)
NIST calibrates and issues a type 30A/T24/13 tungsten strip lamp with a mogul bi-post base.		
39010C	Spectral Radiance Standard, Tungsten Strip Lamp (225 nm to 2400 nm) (other spectral ranges are available under no. 39060S)	16787
NIST calibrates customer supplied integrating sphere sources and maps the source aperture.		
39020C	Spectral Radiance Standard, Integrating Sphere Source (300 nm to 1000 nm in 25 nm steps)	9641
39021C	Spectral Radiance Standard, Integrating Sphere Source (300 nm to 2400 nm in 25 nm steps)	13196
NIST calibrates and issues an 1000 W, tungsten quartz-halogen lamp mounted in a medium bi-post base. The calibrations are performed at 50 cm.		
39030C	Spectral Irradiance Standard, 1000 W Tungsten Quartz-Halogen Lamp (250 nm to 450 nm)	12003
39031C	Recalibration of 1000 W Tungsten Quartz-Halogen Lamp (250 nm to 450 nm)	8578
39032C	Spectral Irradiance Standard, 1000 W Tungsten Quartz-Halogen Lamp (350 nm to 800 nm)	12003
39033C	Recalibration of 1000 W Tungsten Quartz-Halogen Lamp (350 nm to 800 nm)	8578
39040C	Spectral Irradiance Standard, 1000 W Tungsten Quartz-Halogen Lamp (250 nm to 1600 nm)	14945
39041C	Recalibration of 1000 W Tungsten Quartz-Halogen Lamp (250 nm to 1600 nm)	11589
39045C	Spectral Irradiance Standard, 1000 W Tungsten Quartz-Halogen Lamp (250 nm to 2400 nm)	17053
39046C	Recalibration of 1000 W Tungsten Quartz-Halogen Lamp (250 nm to 2400 nm)	13959
NIST calibrates and issues a 30 W deuterium arc lamp mounted in a medium bi-post base.		
39050C	Spectral Irradiance Standard, 30W Deuterium Arc Lamp (200 nm to 400 nm)	15011
39051C	Recalibration of 30 W Deuterium Arc Lamp (200 nm to 400 nm)	11344
39060S	Special Tests of Radiometric Sources	At Cost
E.2 Spectroradiometric Detector Measurements		
39071C	UV Silicon Photodiodes	3855
39072C	Recalibration of UV Silicon Photodiodes	2571
39073C	Visible to NIR Silicon Photodiodes	4661
39074C	Recalibration of Visible to NIR Silicon Photodiodes	3083
39075S	Special Tests of NIR Photodiodes	At Cost
39077C	UV to Near-Infrared Silicon Photodiodes (Hamamatsu S2281)	5533

39078C	Recalibration of UV to Near-Infrared Silicon Photodiodes (Hamamatsu S1337–1010BQ or S2281)	3855
39080S	Special Tests of Radiometric Detectors	At Cost
39081S	Special Tests of Photodetector Responsivity Spatial Uniformity	At Cost
39090S	Special Tests of IR Detectors	At Cost
39100S	Special Tests of Irradiance Detectors	At Cost
39200S	Special Tests of Aperture Area	At Cost

Fees are subject to change without notice.

F. Radiometric Standards in the Ultraviolet

Technical Contact:

Robert E. Vest

Telephone:

(301) 975-3992

Email:

rvest@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8411
Gaithersburg, MD 20899-8411

Charles S. Tarrio

(301) 975-3737

ctarrio@nist.gov

NIST

Steven Grantham

(301) 975-5528

grantham@nist.gov

100 Bureau Drive, Stop 8410

Thomas B. Lucatorto

(301) 975-3734

tlucatorto@nist.gov

Gaithersburg, MD 20899-8410

Please contact the technical staff before shipping instruments or standards to the address listed above.

Standard Detectors in the Far Ultraviolet		
Service ID Number	Description of Services	Fee (\$)
40510C	Detector Standard, Windowless Photodiode (5 nm to 122 nm)	4673
40511C	Recalibration of Detector Standard (5 nm to 122 nm)	4177
40520C	Detector Standard, Windowless Photodiode (18 nm to 122 nm)	3265
40521C	Recalibration of Detector Standard (18 nm to 122 nm)	2769
40530C	Detector Standard, Windowless Photodiode (52 nm to 122 nm)	1856
40531C	Recalibration of Detector Standard (52 nm to 122 nm)	1359
40561C	Recalibration of Detector Standard (116 nm to 254 nm)	1359
40599S	Special Tests on Detectors from the Ultraviolet (254 nm) to the Soft X-Ray Region (5 nm)	At Cost
40600C	Testing the Contamination Potential of Extreme Ultraviolet (EUV) Photoresists	9328
406001S	Special Tests of Extreme Ultraviolet (EUV) Photoresists	At Cost

Fees are subject to change without notice.

G. Laser and Optoelectronic Components Used with Lasers

Technical Contacts:

Marla Dowell
(General Technical Inquiries)

Paul D. Hale
(High Speed Measurements)

Paul Williams
(Laser Radiometry)

Bill Swann
(Optical Fiber and Component Measurements - other than Fiber Power)

Telephone:

(303) 497-7455

(303) 497-5367

(303) 497-3805

(303) 497-7381

Email:

marla.dowell@nist.gov

hale@boulder@nist.gov

paul.williams@nist.gov

william.swann@nist.gov

Mailing Address:

NIST
325 Broadway, MC 815.01
Boulder, CO 80305-3328

Administrative and Logistics:

John Lomax (303) 497-3842 john.lomax@boulder.nist.gov

FAX: (303) 497-4286

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
42110C	Laser Power and Energy Meter (or Detector) Calibrations at a Single Standard Wavelength and Power (See Table 4)	
	CW Laser Power below 2 Watts	4864
	Pulsed Laser Energy (Q-switched YAG) at 1064 nm	5180
	CW Laser Power at 1064 nm above 2 Watts and 10.6 μ m	6313
	Pulsed Laser Energy (Excimer) at 248 nm and 193 nm	6268
42111C	Same as 42110C, Additional Standard Wavelengths or Powers (See Table 4)	
	CW Laser Power below 2 Watts	2432
	Pulsed Laser Energy (Q-switched YAG) at 1064 nm	3560
	CW Laser Power at 1064 nm above 2 Watts and 10.6 μ m above 1 Watt	3724
	Pulsed Laser Energy (Excimer) at 248 nm and 193 nm	4857
42120M	Laser Power and Energy Measurement Assurance Program (MAP)	At Cost
42130C	Optical Fiber Power Meter (or Detectors Used with Lasers) Calibrations at a Single Standard Wavelength and Connector Type (See Table 5)	3554
42131C	Same as 42130C, Additional Standard Wavelengths or Connector Types (See Table 5)	1292
42140M	Optical Fiber Power Meter Measurement Assurance Program (MAP)	At Cost
42150M	Low-Level Laser Measurement Assurance Program (MAP)	At Cost
42151C	Low-Level Laser Radiometer Calibration	At Cost
42155C	Calibration Service of Optoelectronic Frequency Response for Combined Photodiode/RF Power Sensor Transfer Standards	At Cost

42161S	Special Test for Impulse Response Measurements of Detectors Used with Lasers	At Cost
42162S	Special Test for High Accuracy Laser and Optical Fiber Power Measurements	At Cost
42164C	Spectral Responsivity Measurements of Laser and Optical Fiber Power Meters (or Detectors Used with Lasers)	3201
42165S	Special Test for Spatial Uniformity of Laser and Optical Fiber Power Meters and Detectors Used with Lasers	At Cost
42166C	Calibration for Linearity Measurements of Optical Fiber Power Meters (or Detectors Used with Lasers)	At Cost
42167S	Special Test for Linearity Measurements of High-Power Laser Power Meters (or Detectors Used with Lasers)	At Cost
42170S	Special Test for General Laser Measurements, by Prearrangement	At Cost
42180S	Special Test for General Optical Fiber Power Measurements, by Prearrangement	At Cost
42190S	Special Test for Optical Fiber and Fiber Component Measurements (other than Fiber Power), by Prearrangement	At Cost
42210C	Spectral Responsivity Measurements with Curve Fitting of Laser and Optical Meters (or Detectors used with Lasers)	4175
42220C	Calibration Service for Instruments that Measure Laser Beam Diameter	At Cost

Fees are subject to change without notice.

CHAPTER 8

IONIZING RADIATION MEASUREMENTS

A. Radioactivity Sources

<u>Technical Contacts:</u> Lisa R. Karam (All Services) M.P. Unterweger (43030C, 43040C, 43070S, 43090S) Jeffrey T. Cessna (43010C, 43020C, 43060C, 43070S) Lynne King (43030C, 43040C, 43070S, 43090S)	<u>Telephone:</u> (301) 975-5561 (301) 975-5536 (301) 975-5539 (301) 975-5544	<u>Email:</u> lisa.karam@nist.gov munterweger@nist.gov jcessna@nist.gov lynne.king@nist.gov	<u>Mailing Address:</u> NIST 100 Bureau Drive, Stop 8462 Gaithersburg, MD 20899-8462 Attn: Jeffrey Cessna
--	--	--	--

Administrative and Logistics:
 Jeffrey Cessna (301) 975-5539 jcessna@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
43010C	Gamma-Ray-Emitting Radionuclides in Solution (Half Lives Greater than 15 Days)	3388
43020C	Gamma-Ray-Emitting Radionuclides in Solution (Half Lives Less than 15 Days)	5466
43030C	Alpha- and Beta-Particle-Emitting Solid Sources, NIST 2 $\pi\alpha/\beta$ Proportional Counter	2268
43040C	Beta-Particle-Emitting Solid Sources (Activity), NIST 2 $\pi\alpha/\beta$ Proportional Counter	3272
43050C	Mixed Alpha-Emitting Solid Sources, NIST 2 $\pi\alpha/\beta$ Proportional Counter in Conjunction with a Solid State Detector	3499
43060S	Special Tests of Beta-Particle-Emitting Solution Sources, Liquid Scintillation Counting	6177
43070S	Special Tests of Beta-Particle-Emitting Solution Sources, Other Techniques	At Cost
43090S	Special Tests of Alpha-Particle-Emitting Solid Sources	At Cost

Fees are subject to change without notice.

B. Neutron Sources and Neutron Dosimetry

Technical Contacts:

M. Scott Dewey
(All Services Except 44060C)
Alan K. Thompson
(44060C, 44100S)

Telephone:

(301) 975-4843
(301) 975-4666

Email:

mdewey@nist.gov
alan.thompson@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8461
Gaithersburg, MD 20899-8461

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
44010C	Radioactive Neutron Sources Emission Rates (10^5 s^{-1} to 10^9 s^{-1})	6441
44020C	Radioactive Neutron Sources Emission Rates (10^8 s^{-1} to 10^{10} s^{-1})	6441
44060C	Personnel Protection Instrumentation, Californium Source Bare and Moderated	At Cost
44070C	Activation Detector Dosimetry, Thermal Neutrons	At Cost
44080C	Activation Detector Dosimetry, Californium Fission Neutrons	At Cost
44090C	Activation Detector Dosimetry, ^{235}U Cavity Fission Sources	At Cost
44100S	Special Tests of Neutron Sources and Dosimeters	At Cost

Fees are subject to change without notice.

C. Dosimetry of X-Rays, Gamma-Rays, and Electrons

C.1 X-Ray and Gamma-Ray Measuring Instruments

Technical Contacts:

Michelle O'Brien
(46010C-46050S)
Ronaldo Minniti
(46010C-46110C)
Michael G. Mitch
(46010C-47040S)

Telephone:

(301) 975-2014
(301) 975-5586
(301) 975-5491

Email:

michelle.obrien@nist.gov
ronaldo.minniti@nist.gov
michael.mitch@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8460
Gaithersburg, MD 20899-8460
Fax: (301) 869-7682

Please contact the technical staff before shipping instruments or standards to the address listed above.

C.1 X-Ray and Gamma-Ray Measuring Instruments		
Service ID Number	Description of Services	Fee (\$)
Air-Kerma (Exposure)		
46010C	Radiation Detectors—Calibration in ^{60}Co and ^{137}Cs Gamma-Ray Beams, per Detector, per Set-Up, per Beam Code	2088
46011C	Radiation Detectors—Calibration in X-Ray Beams (see Tables 6, 7 and 8), per Detector, per Set-Up, per Beam Code	1997
46020C	Passive Dosimeters—Irradiation of Up to Six, One Beam Quality at One Set-up	2331

46021C	Up to Six Additional Dosimeters at Same Set-up and Beam Quality	1450
46030S	Special Tests of High-Gain Electrometers - Charge Sensitivity, One Set of Switch Positions, with 46010C/46011C, by Prearrangement	1506
46040S	Special Tests of kV Measuring Devices	At Cost
46050S	Special Tests of X-Ray and Gamma-Ray Measuring Instruments	At Cost
Absorbed Dose to Water From ⁶⁰Co Beam		
46110C	Radiation Detectors - Calibration in a ⁶⁰ Co Gamma-Ray Beam	2567
C.2 Sealed Gamma-Ray Sources or Beta-Particle Sources, and Measuring Instruments		
47010C	Gamma-Ray Sources Similar to NIST Standards - ⁶⁰ Co to ¹³⁷ Cs, Having Air-Kerma Strengths 10 $\mu\text{Gy m}^2/\text{h}$ to 1500 $\mu\text{Gy m}^2/\text{h}$; and ¹⁹² Ir Sources of the Same Type Used to Calibrate Reentrant Chamber, Having Air-Kerma Strengths 0.1 $\mu\text{Gy m}^2/\text{h}$ to 30 $\mu\text{Gy m}^2/\text{h}$	3892
47011C	Each Additional Gamma-Ray Source of Same Radionuclide	3741
47020C	¹²⁵ I or ¹⁰³ Pd Sources: Seeds Having Air-Kerma Strengths 0.5 $\mu\text{Gy m}^2/\text{h}$ to 100 $\mu\text{Gy m}^2/\text{h}$	2939
47021C	Each Additional ¹²⁵ I or ¹⁰³ Pd Source of Same Radionuclide/Design Submitted with Above	2847
47030C	Beta-Particle Sources Calibrated for Surface Dose Rate	1211
47035C	Beta-Particle Sources Calibrated for Radiation Protection	985
47036C	Ionization Chamber Calibrated with Beta-Particle Sources for Radiation Protection	985
47040S	Special Tests of Gamma-Ray and Beta-Particle Sources	At Cost

Fees are subject to change without notice.

D. Dosimetry for High-Dose Applications

D.1 Dosimetry of High-Energy Electron Beams

Technical Contacts:

Marc D. Desrosiers
Michael G. Mitch

Telephone:

(301) 975-5639
(301) 975-5491

Email:

marc.desrosiers@nist.gov
michael.mitch@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8460
Gaithersburg, MD 20899-8460

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
D.1 Dosimetry of High-Energy Electron Beams		
48010M	Dose Interpretation of NIST-Packaged Dosimeters Irradiated by Customer - Two Dosimeters	1436
48011M	Each Additional Dosimeter	657

48020S	Special Tests of Electron-Beam Dosimeters	At Cost
--------	---	---------

D.2 Dosimetry of Photon Beams		
49010C	First Irradiation of a Customer Supplied Dosimeter with ⁶⁰ Co Gamma-Rays	1296
49011C	Each Additional Irradiation at Ambient (20 °C to 30 °C) Temperatures	138
49015C	Setup for Each Non-Ambient Irradiation Temperature (–77 °C to +19 °C and +31 °C to +70 °C)	415
49016C	Each Additional Irradiation at Non-Ambient Temperature Under 49015C	200
49020C	Dose Measurement Session of 1 NIST Transfer Dosimeter and Certificate	1403
49021C	Additional Measurement Session of 1 NIST Transfer Dosimeter, Same Certificate with 49020C	657
49022C	Additional Measurement of 1 NIST Transfer Dosimeter, Same Session	138
49030C	Dose Measurement Session of 1 Dosimeter and 90 Day Summary Certificate	1151
49031C	Additional Measurement Session of 1 Dosimeter, Same Certificate with 49030C	349
49032C	Additional Measurement of 1 Dosimeter, Same Session	55
49050S	Special Measurement Services for Dosimeter Response and Dose Distributions	At Cost

Fees are subject to change without notice.

CHAPTER 9

ELECTROMAGNETIC MEASUREMENTS

A. Resistance Measurements

A.1 DC Resistance Standards and Measurements

Technical Contacts:

Randolph E. Elmquist
Marlin E. Kraft

Telephone:

(301) 975-6591
(301) 975-4239

Email:

relmquist@nist.gov
marlin.kraft@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8170
Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather (301) 975-4221 dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Calibration fees are the most critical element in funding the metrology services that we provide, and represent the direct cost of providing calibration services for dc resistors and shunts. These services often reach beyond traceability to include detailed consultation. Currently our fees also must recover some of the rapidly increasing costs of providing year-round, readily accessible services and maintaining state-of-the-art traceability through the quantum Hall effect standard. Customers of our most critical calibration services, NIST Service ID numbers 51130C and 51131C, have benefited the most from our efforts to reduce turn-around time through automation, and to provide the world's best level of uncertainty, while keeping these test fees at a reasonable level.

Service ID Number	Description of Services	Fee (\$)
51100S	Special Resistance Measurements Services, by Prearrangement	At Cost
51110M	Measurement Assurance Program for Resistance	At Cost
51130C	Standard Resistor, Thomas-Type, 1 Ω	3629
51131C	Standard Resistor, Evanohm Wirewound High Precision, 10 k Ω	3407
51132C	Standard Resistor, Four-Terminal 0.0001 Ω	2385
51133C	Standard Resistor, Four-Terminal 0.001 Ω	2027
51134C	Standard Resistor, Four-Terminal 0.01 Ω	2026
51135C	Standard Resistor, Four-Terminal 0.1 Ω	1499
51136C	Standard Resistor, Four-Terminal 1 Ω	1499
51137C	Standard Resistor, Four-Terminal 10 Ω	1499
51138C	Standard Resistor, Four-Terminal 100 Ω	1499
51139C	Standard Resistor, Four-Terminal 1 k Ω	1499
51140C	Standard Resistor, 10 k Ω	1986
51141C	Standard Resistor, 100 k Ω	2455
51142C	Standard Resistor, 1 M Ω	2455

51143C	Standard Resistor, 10 MΩ	2994
51144C	Additional Voltage, 10 MΩ	2349
51145C	Standard Resistor, 100 MΩ	2994
51146C	Additional Voltage, 100 MΩ	2349
51147C	Standard Resistor, 1 GΩ	2994
51148C	Additional Voltage, 1 GΩ	2349
51149C	Standard Resistor, 10 GΩ	3911
51150C	Additional Voltage, 10 GΩ	3030
51151C	Standard Resistor, 100 GΩ	3911
51152C	Additional Voltage, 100 GΩ	3030
51153C	Standard Resistor, 1 TΩ	4081
51154C	Additional Voltage, 1 TΩ	3030
51160C	Standard Resistor for Current Measurements (Shunts) with all determinations at 300 A or Below, One Range, One Current Level	3220
51161C	Standard Resistor for Current Measurements (Shunts), with At Least One Determination Above 300 A (maximum current 2000 A), One Range, One Current Level	3560
51162C	Standard Resistor for Current Measurements (Shunts), Additional Range of a Multi-Range Resistor	1928
51163C	Standard Resistor for Current Measurements (Shunts), Additional Determination at Another Current Level	1928

Fees are subject to change without notice.

A.2 High-Voltage Standard Resistors

Technical Contacts:

Gerald J. FitzPatrick

Telephone:

(301) 975-8922

Email:

gfitzpatrick@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8170
Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather

(301) 975-4221

dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
51210C	High-Voltage Standard Resistors	At Cost

B. Impedance Measurements (Except Resistors)

B.1 Low-Frequency Capacitance and Inductance Measurements and Standards

Technical Contacts:

Andrew D. Koffman

Telephone:

(301) 975-4518

Email:

akoffman@nist.gov

Mailing Address:

NIST

100 Bureau Drive, Stop 8170

Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather

(301) 975-4221

dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
52100S	Special Four Terminal-Pair (4TP) Capacitance and Dissipation Factor Characterization	At Cost
52110S	Special LF Capacitance Measurements, by Prearrangements	At Cost
52120S	Special Measurement Assurance Program for Standard Capacitors (100 pF and 1000 pF, at a Frequency of 1000 Hz)	At Cost
52130C	Fixed, Fused-Silica Dielectric Standard Capacitors (1, 10, and 100) pF, at a Frequency of (100, 400, or 1000) Hz	4140
52131C	Additional Measurement at One of the Above Frequencies	433
52140C	Fixed Three-Terminal, High-Precision Nitrogen Dielectric Standard Capacitors with Coaxial Connectors, Small Uncertainty, (10, 100 and 1000) pF, at a Frequency of (100, 400, or 1000) Hz	2717
52141C	Additional Measurement at One of the Above Frequencies	386
52150C	Physical Tests for Three-Terminal Standard Capacitors with Coaxial Connectors, Large Uncertainty (0.001 pF to 10 000 pF) at a Frequency of (100, 400, or 1000) Hz	2507
52160C	Fixed Three-Terminal Standard Capacitors with Coaxial Connectors, Large Uncertainty (0.001 pF to 10 000 pF) at a Frequency of (100, 400, or 1000) Hz	1721
52161C	Additional Measurement at One of the Above Frequencies	386
52170C	Two- or Three- Terminal Mica Dielectric Standard Capacitors with Binding Post Connectors (0.001 μ F to 1 μ F), at a Frequency of (66, 100, 400, 1000 or 10 000) Hz	2953
52171C	Additional Measurement at One of the Above Frequencies	2425
52176C	Two-Terminal Standard Capacitors with Precision High Frequency (HF) Coaxial Connectors (0.001 pF to 10 000 pF), at a Frequency of 1000 Hz	At Cost
52180C	Fixed Standard Inductors (0.00005 H to 10 H), at a Frequency of (100, 400, 1000, or 10 000) Hz	1768
52181C	Additional Measurement at One of the Above Frequencies	1573
52190S	Special LF Inductance Measurements, by Prearrangement	At Cost

Fees are subject to change without notice.

B.2 High-Frequency Standard Capacitors and Inductors

<u>Technical Contacts:</u>	<u>Telephone:</u>	<u>Email:</u>	<u>Mailing Address:</u>
Ronald A. Ginley	(303) 497-3634	rginley@boulder.nist.gov	NIST M.C. 818.01 325 Broadway Boulder, CO 80305-3325

Administrative and Logistics:
Puanani L. DeLara (303) 497-3753 calibration@boulder.nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
52210S	Two-Terminal Low-Loss Standard Capacitors - 10 kHz to 250 MHz; 1 pF to 20 pF	At Cost
52211S	Two-Terminal Low-Loss Standard Capacitors (High Accuracy) - 10 kHz to 30 MHz, (50, 100, 200, 500, and 1000) pF	At Cost
52221S	Three-Terminal Low-Loss Standard Capacitors (High Accuracy) - 10 kHz to 10 MHz, (10^{-2} , 10^{-1} , 1, 10, 10^2 , and 10^3) pF	At Cost
52310S	Two-Terminal, High- <i>Q</i> Standard Inductors (10^{-2} μ H to 1 H)	At Cost

B.3 Power-Frequency Capacitors

<u>Technical Contacts:</u>	<u>Telephone:</u>	<u>Email:</u>	<u>Mailing Address:</u>
Gerald J. FitzPatrick	(301) 975-8922	gfitzpatrick@nist.gov	NIST 100 Bureau Drive, Stop 8170 Gaithersburg, MD 20899-8170

Administrative and Logistics:
Denise D. Prather (301) 975-4221 dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
52400C	Power-Frequency Capacitors	At Cost

B.4 Q-Standard

<u>Technical Contacts:</u>	<u>Telephone:</u>	<u>Email:</u>	<u>Mailing Address:</u>
Ronald A. Ginley	(303) 497-3634	rginley@boulder.nist.gov	NIST M.C. 818.01 325 Broadway Boulder, CO 80305-3325

Administrative and Logistics:
Puanani L. DeLara (303) 497-3753 calibration@boulder.nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
52710C	Inductive <i>Q</i> -Standards; 50 kHz to 45 MHz, 0.25 μ H to 25 mH	At Cost
52711C	Each Additional Frequency for 52710C	At Cost

C. Voltage Measurements

C.1 DC Voltage Measurements and Standards

Technical Contacts:

Yi-Hua Tang

Telephone:

(301) 975-4691

Email:

ytang@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8170
Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather

(301) 975-4221

dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
53110S	Special DC Voltage Measurements, by Prearrangement	At Cost
53130C	First Saturated Standard Cell in a Group	4962
53131C	Each Additional Cell	3306
53140C	Platinum Resistance Thermometer Temperature Determination for Standard Cell Calibration	1149
53150C	Unsaturated Standard Cells	2785
53160C	Tests of Solid-State Voltage Reference Standard (1 Output, 1 V to 10 V)	2217
53161C	Each Additional Output	1413
53180S	Special Handling (Equipment Pickup or Delivery)	255
53190S	Special Handling (Cleaning, Minor Repair, Return Service Charge)	520

Fees are subject to change without notice.

C.2 AC Voltage Measurements

Technical Contacts:

Bryan C. Waltrip

Telephone:

(301) 975-2438

Email:

bwaltrip@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8170
Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather (301) 975-4221 dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
53200S	Special Tests of High-Accuracy Digital Multimeters, Multifunction Calibrators, by Prearrangement	At Cost
53201S	Special Tests of Low-Voltage AC-DC Transfer Standards, by Prearrangement	At Cost
53202S	Special 25-Point Test of Digital Multimeters (DMMs), by Prearrangement	3872
53203S	Each Additional DMM Test Point for 53202S	At Cost

Fees are subject to change without notice.

C.3 AC-DC Thermal Voltage and Current Converters (to 1 MHz)

Technical Contacts:

Thomas E. Lipe

Telephone:

(301) 975-4251

Email:

tlipe@nist.gov

Mailing Address:

NIST
Building 220, Room B146
100 Bureau Drive, Stop 8170
Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather (301) 975-4221 dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
53310S	Special AC-DC Measurement Services, by Prearrangement	At Cost
53350C	Set-up Charge (No Test Points Included) for a Standard or Standards Set for AC-DC Difference (Voltage or Current)	2546
53351C	First Point for Each Applied Voltage or Current	1048
53352C	Additional Points for Each Applied Voltage and Current Level (Additional Frequency/Voltage or Frequency/Current Points)	76

Fees are subject to change without notice.

D. Precision Ratio Measurements

D.1 Inductive Dividers

Technical Contact:

Scott Shields

Telephone:

(301) 975-4232

Email:

scott.shields@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8170
Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather

(301) 975-4221

dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
54110S	Special Ratio Measurements and Tests of Inductive Voltage Dividers, by Prearrangement	At Cost
54120C	Inductive Voltage Dividers – (Single Frequency, Voltage to be Specified, Each Setting of 3 Most Significant Dials)	4939
54121C	Additional Frequency Points	4939
54130C	Inductive Voltage Dividers – (Single Frequency, Voltage to be Specified, Each Setting of Most Significant Dial Only)	3097
54131C	Additional Frequency Points	3097

Fees are subject to change without notice.

D.2 Resistive Dividers

Technical Contacts:

Gerald J. FitzPatrick

Telephone:

(301) 975-8922

Email:

gfitzpatrick@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8170
Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather

(301) 975-4221

dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
54210C	Resistor and Resistive Dividers, Total Resistance or Voltage Ratio, Two Direct Voltage Levels Between 10 kV and 150 kV	3565
54211S	Special Tests of Resistor and Resistive Dividers at Direct Voltage Levels, by Prearrangement	At Cost
54213S	Special Tests of Resistor and Resistive Dividers at 60 Hz, by Prearrangement	At Cost

Fees are subject to change without notice.

D.3 Capacitive Dividers

Technical Contacts:

Gerald J. FitzPatrick

Telephone:

(301) 975-8922

Email:

gfitzpatrick@nist.gov

Mailing Address:

NIST

100 Bureau Drive, Stop 8170

Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather

(301) 975-4221

dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
54310S	Special Test of Capacitive Dividers at 60 Hz, by Prearrangement	At Cost

D.4 Voltage and Current Transformers

Technical Contacts:

Gerald J. FitzPatrick

Thomas L. Nelson

Telephone:

(301) 975-8922

(301) 975-2986

Email:

gfitzpatrick@nist.gov

tnelson@nist.gov

Mailing Address:

NIST

100 Bureau Drive, Stop 8170

Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather

(301) 975-4221

dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
54510C	Voltage Transformer, Ratio & Phase Angle, at 60 Hz on 1 Range, 1 Secondary Voltage, 1 Burden Primary Vrms \leq 150 kV	At Cost
54520C	Current Transformer, Ratio & Phase Angle, 1 Range at 1 Frequency, 1 Burden, Secondary Currents (0.5, 1, 2, 3, 4, 5) A, Primary Current Not Over 12 000 A	4576
54521C	Current Transformer, Ratio & Phase Angle, 1 Secondary Current, Additional Combination of Range, Frequency, and Burden, Primary Current Not Over 12 000 A	431
54522C	Current Transformer, Ratio & Phase at Each Additional Secondary Current, Same Combination of Range, Frequency, and Burden as 54520C or 54521C	350
54600S	Special Tests of Dividers and Transformers, by Prearrangement	At Cost

Fees are subject to change without notice.

E. Phase Meters and Standards and VOR Measurements

Technical Contacts:

Bryan C. Waltrip

Telephone:

(301) 975-2438

Email:

bwaltrip@nist.gov

Mailing Address:

NIST

100 Bureau Drive, Stop 8170

Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather

(301) 975-4221

dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
55110S	Special Tests of Phase Standards and Related Instruments, by Prearrangement	At Cost
55120C	Phase Meters – One Combination of Input Voltages (0.5 V to 120 V) at One Frequency (2 Hz to 100 kHz) – the Input Voltage Ratio Shall Not Exceed 10	2962
55121C	Phase Meters – Each Additional Combination of Input Voltages (0.5 V to 120 V) at the Same or at a Different Frequency (2 Hz to 100 kHz) – the Input Voltage Ratio Shall Not Exceed 10	943
55130C	Phase Meters – One Additional Combination of One Input Voltage (0.5 V to 120 V) and One Input Current (1 A to 5 A) at One Frequency (2 Hz to 4 kHz)	3985
55131C	Phase Meters – Each Additional Combination of One Input Voltage (0.5 V to 120 V) and One Input Current (0.5 A to 5 A)	1077
55140C	Phase Meters – One Input Voltage (120 V to 240 V) and Another Input Voltage (120 V to 240 V) at One Frequency (2 Hz to 5 kHz)	3985
55141C	Phase Meters – Each Additional Combination of One Input Voltage (120 V to 240 V) and Another Input Voltage (120 V to 240 V) at the Same or at a Different Frequency (2 Hz to 5 kHz)	1077

Fees are subject to change without notice.

F. Power and Energy Measurements, Low-Frequency

Technical Contacts:

Thomas L. Nelson
Gerald J. FitzPatrick

Telephone:

(301) 975-2986
(301) 975-8922

Email:

tnelson@nist.gov
gfitzpatrick@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8170
Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather (301) 975-4221 dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
56110S	Special Test of AC-DC Wattmeters, by Prearrangement	At Cost
56200C	Watt, Watthour, Var, Varhour Meter, Initial Two Determinations of Same Meter at 60 Hz	4146
56201C	Each Additional Determination, Same Meter at 50 Hz	248
56202C	Initial Two Determinations of One or Two Meters Run Simultaneously with the First (56200C)	3796
56210M	Measurement Assurance Program for Watthour Meters	5384
56220S	Special Tests of Watthour Meter with Pulse Output; 120 Volts, 5 Amperes, 60 Hz at 0.5 Lag, Unity and 0.5 Lead Power Factors	1749
56230S	Special Test of Phasor Measurement Units, PMUs	At Cost

Fees are subject to change without notice.

G. RF, Microwave and Millimeter-Wave Measurements

G.1 Thermistor Detectors

Technical Contacts:

Ronald A. Ginley
Thomas P. Crowley

Telephone:

(303) 497-3634
(303) 497-4133

Email:

rginley@boulder.nist.gov
crowley@boulder.nist.gov

Mailing Address:

NIST
325 Broadway, MC 818.01
Boulder, CO 80305-3328

Administrative and Logistics:

Puanani L. DeLara (303) 497-3753 calibration@boulder.nist.gov
Fax: (303) 497-3970

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
The following tests are for 50 Ω thermistor and thermoelectric detectors with coaxial connectors.		
61100S	Measurement setup charge (applies to all coaxial power measurements—one setup charge for multiple detectors with the same connectors and frequencies ¹)	2912
61110S	Coaxial Detectors in the Frequency Range from 0.1 MHz to 10 MHz	3325
61120S	Coaxial Detectors at user Selected Frequencies in the appropriate Frequency Range for the Connector Type ² . Up to 20 Frequency Points	3600
61121S	Coaxial Detectors at user Selected Frequencies in the appropriate Frequency Range for the Connector Type ² . From 20 to 40 Frequency Points	3923
61122S	Coaxial Detectors at user Selected Frequencies in the appropriate Frequency Range for the Connector Type ² . From 40 to 120 Frequency Points	4244

61123S	Coaxial Detectors at user Selected Frequencies in the appropriate Frequency Range for the Connector Type ² . More than 120 Frequency Points	4889
61137C	NIST Model CN Coaxial Detectors at 21 Frequencies within the Frequency Range of 50 MHz to 18 GHz	8227
61138C	NIST Model CN Coaxial Detectors at Single Customer Selected Frequency within the Frequency Range of 50 MHz to 18 GHz	51
The following tests are for thermistor detectors with waveguide flanges.		
61140S	Measurement setup charge (applies to all waveguide power measurements EXCEPT WR15—one charge for multiple detectors with the same connectors and frequencies ¹)	5488
61141S	Measurement setup charge (applies to all WR15 waveguide power measurements—one charge for multiple detectors with the same connectors and frequencies ¹)	4284
61142S	Rectangular Waveguide Detectors with WR90 Flanges ²	3518
61143S	Rectangular Waveguide Detectors with WR62 Flanges ²	3518
61144S	Rectangular Waveguide Detectors with WR42 Flanges ²	3518
61145S	Rectangular Waveguide Detectors with WR28 Flanges ²	3944

61146S	Rectangular Waveguide Detectors with WR22 Flanges ²	4399
61147S	Rectangular Waveguide Detectors with WR15 Flanges ²	6685
61148S	Rectangular Waveguide Detectors with WR10 Flanges ²	6685
Miscellaneous Tests		
61190S	Special Microwave and RF Power Measurement Services, by Prearrangement	At Cost

Fees are subject to change without notice.

¹ Only one setup charge is necessary for multiple detectors sent in at the same time with the same connector type and measurement frequencies.

² Measurement Frequencies

G.2 Scattering Parameters of Passive One and Two-Port Devices

<u>Technical Contacts:</u>	<u>Telephone:</u>	<u>Email:</u>	<u>Mailing Address:</u>
Ronald A. Ginley	(303) 497-3634	rginley@boulder.nist.gov	NIST 325 Broadway, MC 818.01 Boulder, CO 80305-3328

Administrative and Logistics:
Puanani L. DeLara (303) 497-3753 calibration@boulder.nist.gov
Fax: (303) 497-3970

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
61290S	Special Microwave and RF Scattering-Parameter Measurement Services, by Prearrangement	At Cost

Fees are subject to change without notice.

G.3 Thermal Noise Measurements

<u>Technical Contacts:</u>	<u>Telephone:</u>	<u>Email:</u>	<u>Mailing Address:</u>
David Walker	(303) 497-5490	dwalker@boulder.nist.gov	NIST 325 Broadway, MC 818.01 Boulder, CO 80305-3328
James Randa	(303) 497-3150	randa@boulder.nist.gov	

Administrative and Logistics:
Puanani L. DeLara (303) 497-3753 calibration@boulder.nist.gov
Fax: (303) 497-3970

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Freq.	Connector Type	Device Requirements/Service	Fee (\$)
-------------------	-------	----------------	-----------------------------	----------

61410S	30 MHz 60 MHz	Coaxial N Precision (PIN) GPC 3.5 (PIN) GPC 7 14 mm	Temperature < 15 000 K (ENR < 17 dB) VSWR < 1.2	
	Set Up Charge, per order			3495
	Per Frequency			5569
61420S	1.0 GHz to 12.4 GHz Continuous Frequencies	Coaxial 14 mm (1 to 4 GHz) GPC 7 N Precision (PIN) GPC 3.5 (PIN) GPC 2.4 (PIN) (8 GHz to 12.4 GHz)	Temperature < 15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
	Set Up Charge, per order			5776
	Per Frequency			695
61425S	12.4 GHz to 18.0 GHz Continuous Frequencies	Coaxial GPC 7 N Precision (PIN) GPC 3.5 (PIN) GPC 2.4 (PIN)	Temperature < 15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
	Set Up Charge, per order			7831
	Per Frequency			4474
61430S	18.0 GHz to 26 GHz Continuous Frequencies	Coaxial GPC 3.5 (PIN) GPC 2.4 (PIN)	Temperature < 15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
	Set Up Charge, per order			7648
	Per Frequency			4326

61435S	26.5 GHz to 40 GHz Continuous Frequencies	<i>Coaxial</i> GPC 2.4 (PIN)	Temperature < 15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
	Set Up Charge, per order			11376
	Per Frequency			5915
61450S	8.2 GHz to 12.4 GHz Continuous Frequencies	<i>Waveguide</i> WR 90	Temperature <15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
	Set Up Charge, per order			6505
	Per Frequency			695
61455S	12.4 GHz to 18.0 GHz Continuous Frequencies	<i>Waveguide</i> WR 62	Temperature < 15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
	Set Up Charge, per order			7831
	Per Frequency			4242
61460S	18.0 GHz to 26.0 GHz Continuous Frequencies	<i>Waveguide</i> WR 42	Temperature < 15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
	Set Up Charge, per order			7831
	Per Frequency			4242
61465S	26.5 GHz to 40.0 GHz Continuous Frequencies	<i>Waveguide</i> WR 28	Temperature < 15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
	Set Up Charge, per order			8559
	Per Frequency			4242
61470S	33.0 GHz to 50.0 GHz Continuous Frequencies	<i>Waveguide</i> WR 22	Temperature <15 000 K (ENR < 17 dB) Reflection Coefficient <0.2	
	Set Up Charge, per order			7831
	Per Frequency			4242
61475S	50.0 GHz to 65.0 GHz Continuous Frequencies	<i>Waveguide</i> WR 15	Temperature < 15 000 K (ENR , 17 dB) Reflection Coefficient < 0.2	
	Set Up Charge, per order			10532
	Per Frequency			6844
61495S	Special Noise Temperature Measurements, by Prearrangement			At Cost

Fees are subject to change without notice.

H. Electromagnetic Field Strength and Antenna Measurements

H.1 Microwave Antenna Parameter Measurements

<u>Technical Contacts:</u>	<u>Telephone:</u>	<u>Email:</u>	<u>Mailing Address:</u>
Perry F. Wilson (63100S–63400S)	(303) 497-3406	pfw@boulder.nist.gov	NIST 325 Broadway, MC 818.02 Boulder, CO 80305-3328
Jeff Guerrieri (63100S)	(303) 497-3863	jeff.guerrieri@nist.gov	
Michael H. Francis (63200S)	(303) 497-5873	mfrancis@boulder.nist.gov	

Administrative and Logistics:
Puanani L. Delara (303) 497-3753 calibration@boulder.nist.gov
Fax: (303) 497-3970

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
63100S	Gain and Polarization Calibrations of Standard Antennas Using Extrapolation Range	At Cost
63200S	Measurement of Pattern, Gain, and Polarization of Arbitrary Antennas Using Near-Field Scanning Techniques	At Cost
63400S	Special Consulting, Advisory, and Other Services	At Cost

H.2 Field Strength Parameter Measurements

<u>Technical Contacts:</u>	<u>Telephone:</u>	<u>Email:</u>	<u>Mailing Address:</u>
Dennis G. Camell	(303) 497-3214	camell@boulder.nist.gov	NIST
Perry F. Wilson	(303) 497-3406	pfw@boulder.nist.gov	325 Broadway, MC 818.02 Boulder, CO 80305-3328

Administrative and Logistics:
Puanani L. DeLara (303) 497-3753 calibration@boulder.nist.gov
Fax: (303) 497-3970

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
64100S	Special Test Services for Antenna/Field Strength/M Measurement, Using the Transverse Electromagnetic (TEM) Cell Method (10 kHz to 300 MHz)	At Cost
64300S	Special Test Services for Antenna/Field Strength/Reflectivity Measurements, Utilizing the Anechoic Chamber and Standard Field Method	At Cost

I. High-speed Repetitive Waveform Measurements

Technical Contacts:

Paul Hale

Telephone:

(303) 497-5367

Email:

hale@boulder.nist.gov

Mailing Address:

NIST
325 Broadway, MC 815.01
Boulder, CO 80305-3328

Administrative and Logistics:

John Lomax

(303) 497-3842

john.lomax@nist.gov

Fax: (303) 497-4286

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
65200S	Fast Repetitive Waveforms	At Cost
65400S	Fiber-optic time delay (formerly Pulse Time Delay Interval)	At Cost

J. Pulse Waveform Measurements

Technical Contacts:

Thomas Nelson

Telephone:

(301) 975-2986

Email:

thomas.nelson@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8170
Gaithersburg, MD 20899-8170

Fax: (301) 926-3972

Administrative and Logistics:

Denise Prather

(301) 975-4221

dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
65250S	Repetitive Pulse Waveform Measurements, Including Settling Parameters	At Cost
65500S	Peak-to-Peak Detector Calibration at One Frequency Selected from Those Give in Table 9.23 at 1.2V	At Cost
65501S	Additional Frequency for Peak-to-Peak Detector in 65500S	At Cost

CHAPTER 10

TIME AND FREQUENCY MEASUREMENTS

A. Broadcast and Measurement Services

<u>Technical Contacts:</u> Michael A. Lombardi (Frequency) Marc A. Weiss (Time) John Lowe Stefania Romisch	<u>Telephone:</u> (303) 497-3212 (303) 497-3261 (303) 497-5453 (303) 497-3446	<u>Email:</u> lombardi@boulder.nist.gov mweiss@boulder.nist.gov lowe@boulder.nist.gov stefania.romisch@nist.gov	<u>Mailing Address:</u> NIST 325 Broadway, MC 847.40 Boulder, CO 80305-3328
---	--	--	---

Administrative and Logistics:
 Trudi Peppler (303) 497-3338 tpeppler@boulder.nist.gov
Fax: (303) 497-6461

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
Broadcast Services (WWW, WWVH, WWVB, GOES, ACTS, and NTS)		
76100C	Frequency Measurement and Analysis Service (FMAS), Frequency Delivered to User's Site	Initial One-Time Fee: 1564 Monthly Charge: 513
76101C	Time Measurement and Analysis Service (TMAS)	Initial One-Time Fee: 1558 Monthly Charge: 771
76110S	Global Time Service, Frequency and Time delivered to User's Site	15103 per year
76120S	Characterization of Global Positioning System (GPS) Satellite Receivers	At Cost

B. Calibration and Characterization of Oscillators and Amplifiers

Technical Contacts:

David Howe
Stefania Romisch

Telephone:

(303) 497-3277
(303) 497-3446

Email:

dhowe@boulder.nist.gov
stefania.romisch@nist.gov

Mailing Address:

NIST
325 Broadway, MC 847
Boulder, CO 80305-3328

Administrative and Logistics:

Trudi Peppler (303) 497-3338 tpeppler@boulder.nist.gov
Fax: (303) 497-6461

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
77100C	Oscillator Frequency Calibration	At Cost
77110C	Characterization of Atomic Frequency Standards	At Cost
77120C	Characterization of Oscillators: Time Domain	At Cost
77130C	Characterization of Oscillators and Amplifiers: Phase Noise in the Frequency Domain	At Cost
77131C	Characterization of Oscillators and Amplifiers: Amplitude Noise in the Frequency Domain	At Cost

C. Test of PM/AM Noise Measurement Systems

Technical Contact:

David Howe

Telephone:

(303) 497-3277

Email:

dhowe@boulder.nist.gov

Mailing Address:

NIST
325 Broadway, MC 847.30
Boulder, CO 80305-3328

Administrative and Logistics:

Trudi Peppler (303) 497-3338 tpeppler@boulder.nist.gov
Fax: (303) 497-6461

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
77135C	Tests of RF PM/AM Noise Measurement Systems: On-Site Tests	At Cost
77136C	Tests of Microwave PM/AM Noise Measurement Systems: On-Site Tests	At Cost
77140S	Special Time/Frequency Measurements: Oscillators and Other Components	At Cost

CHAPTER 11

SEMINARS

The following announcements concern notification of changes in services and information about future NIST Measurement Seminars. General policy questions regarding NIST measurement services should be referred to the Calibration Program.

NIST MEASUREMENT SEMINARS

NIST holds seminars and workshops that provide advice and assistance on measurements and calibrations. This affords laboratories outside NIST an opportunity to learn how to make measurements consistent with national standards which NIST maintains. Participation is open to a limited number of people who have the appropriate education, work experience, and current profession in measurement and standards laboratory activities.

Each seminar lasts from one to five days and is devoted to lectures, group discussions, and laboratory demonstrations. A course may be cancelled if registration is insufficient. However, in the past, requests for enrollment have nearly always exceeded the numbers that could be accommodated.

Acceptance letters will be mailed no later than 4 weeks prior to the scheduled date of the course. Detailed information on schedules and housing will be included. Those accepted will be expected to study the assigned reading material before coming to the course and should be prepared to discuss their own experiences with related problems.

See the Weights and Measures Program web site www.nist.gov/pml/wmd/index.cfm for the National Conference on Weights and Measures (NCWM) Calendar of Events for other training not listed here.

NIST offers conferences and workshops throughout the year. To see the latest listing go to www.nist.gov for upcoming NIST Conferences and Events.